

Intellinet Gigabit High-Power PoE+ Injector, 1 x 30 W, IEEE 802.3at/af Power over Ethernet (PoE+/PoE)

Gamintojas: **INTELLINET** · Modelis: **560566** · EAN: **766623560566** · Prekės kodas: **945542**



34,90 €

Kaina su PVM

Be PVM: **28,84 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Save time and money by delivering data and power via existing network cables
- ✓ Power output of up to 30 watts
- ✓ Supports all IEEE 802.3at- and IEEE 802.3af-compliant PoE devices (Wireless LAN access points and bridges, VoIP [Voice over Internet Protocol] telephones, IP surveillance cameras)
- ✓ Supports IEEE 802.3at/af detection and short circuit, overload and high-voltage protection
- ✓ Fanless design ideal for silent operation
- ✓ Three-Year Warranty



Aprašymas

Reduce costs by using existing Cat5 cable to provide both power and data.

The Intellinet Network Solutions 1-Port Gigabit High-Power PoE+ Injector allows you to connect your IEEE 802.3af/at-compliant products to a non-PoE LAN switch port. The PoE Injector can be used to connect a wireless access point, IP phone, network camera or any IEEE 802.3af/at-powered device (PD) to a switch. The device has an output power rating of up to 30 watts. That's enough for even power-hungry PoE devices.

Reduce Wiring Costs

No need to run AC power lines for your wireless access point, network camera or IP phone. Simply connect the PoE Injector to the LAN switch port, and use the existing Cat5 cabling to deliver DC power as well as transfer data.

Protect Your Equipment

Now that you are running DC power to your networked equipment through the Cat5e/6 cabling, you need to be sure that the products are protected from power problems. The PoE Injector was designed to protect equipment from short circuits (short GRND), current overloads and high voltages.

Techninė specifikacija

Network	
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u
Cable types supported	Cat5, Cat5e
Features	
Product colour	Black
Housing material	Metal
LED indicators	PoE, Power
Power protection features	Over voltage, Overload, Short circuit
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
Power	
Input voltage	100 - 240 V
Power consumption (max)	42 W
Certificates	
Compliance certificates	CE, RoHS, Federal Communications Commission (FCC)
Certification	FCC Class A Subpart B, CE, RoHS, UKCA, NDAA
Operational conditions	
Operating temperature (T-T)	5 - 45 °C
Operating relative humidity (H-H)	10 - 90%

Storage temperature (T-T)	-20 - 55 °C
---------------------------	-------------

Weight & dimensions

Width	72 mm
Depth	154 mm
Height	35 mm
Weight	790 g

Packaging content

Number of products included	1 pc(s)
Manual	Yes

Logistics data

Harmonized System (HS) code	85044095
-----------------------------	----------

Dokumentai ir vaizdo įrašai

› [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

IC Intracom Vertriebs GmbH

Löhbacher Str. 7, D-58553 Halver, DE

[intellinetnetwork.eu](mailto:info@shopro.lt)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt