

Intellinet Gigabit High-Power PoE+ Injector, 1 x 30 W Port, IEEE 802.3at/af Compliant, Plastic Housing

Gamintojas: **INTELLINET** · Modelis: **561518** · EAN: **766623561518** · Prekės kodas: **945543**



43,90 €

Kaina su PVM

Be PVM: **36,28 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Saves time and money by delivering data and power via existing network cables
- ✓ IEEE 802.3at compliant (PoE+)
- ✓ Power output up to 30 watts
- ✓ Distance support: up to 100 m (328 ft.)
- ✓ Supports all IEEE 802.3at- and IEEE 802.3af-compliant PoE devices (Wireless LAN access points and bridges, VoIP [Voice over Internet Protocol] telephones, IP surveillance cameras and more)
- ✓ Supports IEEE 802.3at/af detection and short circuit, overload and high-voltage protection
- ✓ Internal power supply
- ✓ Fanless design ideal for silent operation
- ✓ CE-approved



Aprašymas

Provide both power and data to a Powered Device (PD) using existing Cat5 cable and this PoE Injector.

The Intellinet Network Solutions Gigabit High-Power PoE+ Injector lets you connect your IEEE 802.3af/at-compliant product to a non-PoE LAN switch port. The PoE Injector can power and supply a network connection to a wireless access point, IP phone, network camera or any IEEE 802.3af/at-powered PD. This injector has an output power rating up to 30 watts. That's enough for even power-hungry PoE devices.

Reduce Wiring Costs.

There's no need to run AC power lines to get your PD set up and ready to do what it's supposed to. Simply connect the PoE Injector to the LAN switch port, and use the existing Cat5 cabling to deliver DC power as well as transfer data.

Protect Your Equipment.

Once DC power is connected to your networked equipment through the Cat5e/6 cabling, the Intellinet Network Solutions PoE Injector ensures that your products are protected from power problems like short circuits (short GND), current overloads and high voltages.

Techninė specifikacija

Network	
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x
Cable types supported	Cat5, Cat5e
Features	
Maximum operating distance	100 m
LED indicators	Yes
Power protection features	Over voltage, Overload, Short circuit
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
Power	
Output power	30 W
Input voltage	100-240 V
Input frequency	50-60 Hz
Power consumption (max)	35 W
Certificates	
Compliance certificates	CE, RoHS, Federal Communications Commission (FCC)
Certification	FCC, CE, UL
Operational conditions	

Operating temperature (T-T)	0 - 50 °C
Operating temperature (T-T)	-20 - 80 °F
Operating relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	67 mm
Depth	136 mm
Height	34 mm
Weight	190 g
Packaging content	
Manual	Yes
Logistics data	
Harmonized System (HS) code	85044095
Matmenys ir svoris	
Svoris	0,36kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

IC Intracom Vertriebs GmbH

Löhbacher Str. 7, D-58553 Halver, DE

[intellinetnetwork.eu](mailto:info@shopro.lt)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt