

Intellinet 2-Port Gigabit High-Power PoE+ Extender Repeater, IEEE 802.3at/af Power over Ethernet (PoE+/PoE), metal

Gamintojas: **INTELLINET** · Modelis: **561266** · EAN: **766623561266** · Prekės kodas: **945544**



60,90 €

Kaina su PVM

Be PVM: **50,33 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Connects and powers two PoE devices such as network cameras, Wireless Access Points or VoIP phones from one PoE injector or PoE switch PSE port
- ✓ Doubles the connection distance between PoE source and device from 100 m (328 ft.) to 200 m (656 ft.)
- ✓ Saves time and money by delivering data and power via existing network cables
- ✓ Supports 10/100/1000 Mbps data rates and delivers up to 25 W to connected PoE devices
- ✓ PoE awareness ensures that power is only sent to IEEE 802.3af/at-compliant devices; non-PoE devices only receive data
- ✓ Requires no additional power supply; draws power directly from the PoE input
- ✓ Compatible with IEEE 802.3at/af-compliant PoE injectors and PoE switches (PSE)
- ✓ Compatible with IEEE 802.3at/af-compliant powered devices (PD)
- ✓ PoE-Powered 3-Port Gigabit Switch with PoE Passthrough
- ✓ 6 Gbps switch fabric



Aprašymas

Extend the range of a PoE connection.

The Intellinet Network Solutions 2-Port Gigabit High-Power PoE+ Extender Repeater extends connection distances from a PoE source to two output devices up to 100 m (328 ft.) via Cat5e or Cat6 cable. The PoE+ extender does not need any additional power supply, as it draws the power it needs from the PoE input.

Reduce Wiring Costs

Avoid the expense of running AC power lines for your wireless access point, network camera or IP phone. Simply connect the PoE Extender to the LAN switch port and use the existing Cat5e/6/6a cabling to deliver DC power as well as transfer data.

Power over Ethernet 802.3at Compliant

The Intellinet Network Solutions 2-Port Gigabit High-Power PoE+ Extender Repeater supports the IEEE 802.3at protocol. The repeater forwards data at Gigabit speeds and offers up to 30 watts of input power to a connected IEEE 802.3af- or IEEE 802.3at-compliant device. The cable length on both ends can be up to 100 meters (328 ft.), bringing the total distance between PoE source and device to 200 m (656 ft.).

Simple Installation

Simply connect the "PoE In" port with your PoE injector or PoE switch, and connect the "PoE Out" ports with the PoE devices that you wish to connect (e.g., a VoIP phone and a PoE network camera). That's it. This product was designed to be as easy as possible to set up and use.

Techninė specifikacija

Management features	
Switch type	Unmanaged
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	3
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Cable types supported	Cat5, Cat5e
Data transmission	
MAC address table	2048 entries
Switching capacity	6 Gbit/s
Store-and-forward	Yes
Jumbo frames support	Yes
Packet buffer memory	0.256 MB
Design	
Product colour	Black
Housing material	Metal

LED indicators	Yes
Power	
Power consumption (typical)	30 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) power per port	25 W
Operational conditions	
Operating temperature (T-T)	-10 - 45 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	140 mm
Depth	77 mm
Height	28 mm
Weight	240 g
Packaging content	
Manual	Yes
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC)
Certification	FCC Class A, CE
Logistics data	
Harmonized System (HS) code	85176990
Matmenys ir svoris	
Svoris	0,36kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

IC Intracom Vertriebs GmbH

Löhbacher Str. 7, D-58553 Halver, DE

[intellinetnetwork.eu](mailto:info@shopro.lt)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt