

Intellinet 4-Port Gigabit Ultra PoE Extender, Adds up to 100 m (328 ft.) to PoE Range, 90 W PoE Power Budget, Four PSE Ports with up to 30 W Output, IEEE 802.3bt/at/af Compliant, Metal Housing

Gamintojas: **INTELLINET** · Modelis: **561617** · EAN: **766623561617** · Prekės kodas: **946514**



94,90 €

Kaina su PVM

Be PVM: **78,43 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Doubles the maximum connection distance between PoE source and device from 100 m (328 ft.) to 200 m (656 ft.)
- ✓ Connects and powers four PoE devices such as network cameras, wireless access points or VoIP phones, from one PoE injector or PoE switch PSE port
- ✓ Delivers up to 90 W to four connected PoE devices with up to 30 W per port
- ✓ Supports 10/100/1000 Mbps data rates
- ✓ Total PoE power budget of 90 watts
- ✓ Saves time and money by delivering data and power via existing network cables
- ✓ PoE awareness, ensuring that power is only sent to IEEE 802.3at/af-compliant devices; non-PoE devices only receive data
- ✓ Short-circuit, overload and high-voltage protection
- ✓ Grounding point to protect equipment from external electrical surges
- ✓ Requires no additional power supply; draws power directly from the PoE input



Aprašymas

The Gigabit PoE Extender — for doubling the range of a Gigabit Power over Ethernet connection

The Intellinet Network Solutions 4-Port Gigabit Ultra PoE Extender adds up to 100 m (328 ft.) to the connection distance from a PoE source to four output devices via Cat5e or Cat6 cable. This PoE extender does not need an additional power supply since it draws its power from the PoE input.

Reduced Wiring Costs

This Ultra PoE Extender helps avoid the expense of running AC power lines for a wireless access point, network camera or IP phone. Simply connect the PoE Extender to the LAN switch port through existing Cat5e/6/6a cables to deliver DC power as well as transfer data.

Power over Ethernet 802.3bt Compliant

The Intellinet Network Solutions 4-Port Gigabit Ultra PoE Extender supports the IEEE 802.3bt protocol over four pairs (4PPoE), which allows for a power input of 90 W. It forwards data at Gigabit speeds and offers up to 30 watts per port to a connected IEEE 802.3at- or IEEE 802.3af-compliant device. The cable length on both ends can be up to 100 meters (328 ft.), bringing the total distance between PoE source and device to 200 m (656 ft.).

Simple Installation

This PoE Extender was designed to be as easy as possible to set up and use. All it takes to have it up and running is to connect its "PoE In" port to your PoE injector or PoE switch and to connect the "PoE Out" ports to the PoE devices you want to connect (e.g., a VoIP phone and a PoE network camera).

Techninė specifikacija

Performance	
Type	Network transmitter
Maximum transfer distance	100 m
Data transfer rate	10000 Mbit/s
Cable types supported	Cat5e
Ethernet LAN data rates	10,100,1000 Mbit/s
Jumbo frames support	Yes
Duplex system	Full
MAC address table	2048 entries
Flow control support	Yes
Network	
Cabling technology	10/100/1000Base-T(X)
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x
Ports & interfaces	
Ethernet LAN (RJ-45) ports	5
Power over Ethernet (PoE) ports quantity	4

Design

Product colour	Black
Housing material	Metal
LED indicators	Activity, Link, PoE
Certification	FCC A, CE

Power

Power over Ethernet (PoE)	Yes
Total Power over Ethernet (PoE) budget	90 W
Power over Ethernet (PoE) voltage range	44 - 57 V

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-10 - 70 °C
Operating relative humidity (H-H)	20 - 85%

Weight & dimensions

Width	130 mm
Depth	86 mm
Height	29 mm
Weight	337 g

Packaging content

Manual	Yes
--------	-----

Certificates

Compliance certificates	CE, RoHS, Federal Communications Commission (FCC), UL
-------------------------	---

Logistics data

Harmonized System (HS) code	85176990
-----------------------------	----------

Matmenys ir svoris

Svoris	0,43kg
--------	--------

Dokumentai ir vaizdo įrašai

- › Naudojimo instrukcija
- › Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

IC Intracom Vertriebs GmbH

Löhbacher Str. 7, D-58553 Halver, DE

intellinetnetwork.eu

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt