Lindy 150m Cat.6 DisplayPort 1.2, USB, IR and RS-232 HDBaseT KVM Extender

Gamintojas: **LINDY** · Modelis: **39385** · EAN: **4002888393850** · Prekės kodas: **946594**



368.90€

Kaina su PVM

Be PVM: **304.88€**

In Stock

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Extends DisplayPort signals up to 150m distances over Cat.6 network cable via HDBaseT technology
- ✓ Supports resolutions up to 4K@60Hz 4:4:4
- ✓ USB ports for mouse and keyboard connection
- ✓ Bi-directional IR and RS-232 control and PoC (Power over Cable) function
- ✓ 2 year warranty






Aprašymas

The Lindy Cat.6 DisplayPort 1.2 and USB HDBaseT KVM Extender is an high-end, reliable solution for extending high quality 4K DisplayPort signals over long distances with standard Cat.6 network cable.

The following distance and resolution combinations are possible when using high quality Cat.6 U/UTP or F/UTP solid core cable:

- 150m: 1920x1080@60Hz 4:4:4 8bit- 100m: 3840x2160@60Hz 4:4:4 8bit

Supporting resolutions up to 4K Ultra HD, video can be viewed in stunning clarity, this provides a reliable solution for creating eye-catching digital signage in retail, immersive displays at events or engaging setups in larger conference rooms or lectures halls.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

This extender also supports lossless audio formats including Dolby TrueHD and DTS-HD to add powerful multi-channel sound to video content, providing an enhanced experience and sense of immersion for the viewer. USB KM connectivity via 2 USB HID ports allow for a keyboard and mouse at the receiver to control a DP equipped PC from a remote PC setup, which can be stored in a secure or controlled temperature environment, while seamlessly providing consistent video content from the source.

Featuring bi-directional IR ports at both sides of the setup, the source equipment can be seamlessly controlled from the display side, and the display can also be controlled from the DisplayPort source device. RS-232 connections also allow for integration into pre-installed control systems. In addition, PoC (Power over Cable) functionality provides additional flexibility. This allows power to be supplied alongside data through Cat.6 network cable in a point-to-point connection between the transmitter and receiver, meaning only a single power supply is required at the transmitter or receiver unit. Ideal for example when power outlets are limited at the receiver end of the installation.

The extenders built-in EDID function ensures maximum compatibility with the display or projector at the receiver, further enhancing this system focus on providing high quality 4K DP content over distances easily and with minimum hassle for the user.

HDBaseT is a globally recognised standard for high quality distribution of AV content and other technologies, including power and control, over longer distances via low cost Cat.6 or above cable.

HDBaseT and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance.

Please Note: keep the units in a cool and dry place. If the extender has to stay in a closed and small area, please ensure that the operating temperature is within the range shown in technical specifications.

Techninė specifikacija

Features	
Type	Transmitter & receiver
Connectivity technology	Wired
Maximum transfer distance	150 m
Cable types supported	Cat6
Maximum digital resolution	3840 x 2160 pixels
Maximum refresh rate	60 Hz
Colour depth	8 bit
Product colour	Black
Material	Metal
LED indicators	Power
Transmitter	
Transmitter video port type	DisplayPort
Transmitter local video port	Yes
Transmitter local video port type	DisplayPort
Transmitter local keyboard/mouse port type	USB
RJ-45 ports quantity (transmitter)	1
Receiver	
Receiver local video port type	DisplayPort
Receiver local keyboard/mouse port type	USB

RJ-45 ports quantity (receiver)	1
Receiver local video ports quantity	1
Ports & interfaces	
USB port type	USB Type-A/USB Type-B
RS-232 ports	2
Remote (IR) input	2
Remote (IR) output	2
USB 1.1 ports quantity	5
Power	
Input current	1 A
DC-in jack	Yes
DC voltage	24 V
Weight & dimensions	
Transmitter width	14 cm
Transmitter depth	6.5 cm
Transmitter height	1.8 cm
Transmitter weight	800 g
Receiver width	14 cm
Receiver depth	6.5 cm
Receiver height	1.8 cm
Receiver weight	800 g
Packaging data	
Package width	245 mm
Package depth	75 mm
Package height	185 mm
Package weight	1.02 kg
Packaging content	
AC adapter included	Yes
Cables included	USB
Manual	Yes
Mounting bracket(s) included	Yes
Included power plug types	AU, EU, UK, US
Operational conditions	
Operating temperature (T-T)	0 - 40 °C

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 90%
Storage relative humidity (H-H)	20 - 90%
Other features	
Compliance certificates	Federal Communications Commission (FCC), UKCA, CE, REACH, RoHS
Sustainability	
Sustainability compliance	Yes

Dokumentai ir vaizdo įrašai

- User manual
- Declaration of conformity

Gamintojo ir saugos informacija

MANUFACTURER

LINDY International Ltd.
Sadler Forster Way Unit 103, TS17 9JY Stockton-on-Tees, GB
lindy.com

EU RESPONSIBLE PERSON

LINDY-Elektronik GmbH
Markircher Str. 22, 68229 Mannheim, DE
lindy.com

DISTRIBUTOR

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

- Declaration of conformity