

StarTech.com 2-Port DisplayPort KVM Switch, 8K 60Hz / 4K 144Hz, Single Display, DP 1.4, 2x USB 3.0 Ports, 4x USB 2.0 HID Ports, Push-Button & Hotkey Switching, TAA Compliant - OS Independent, Metal Housing

Gamintojas: **STARTECH** · Modelis: **D86A2-2-PORT-8K-KVM** · EAN: **065030894906** · Prekės kodas: **946907**



439,90 €

Kaina su PVM

Be PVM: **363,55 €**

[Sandėlyje](#)



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ **8K 60HZ WITH HDR:** Fast switch between two USB-A and DisplayPort-enabled desktops to share a keyboard, mouse, audio device, and a single 8K 60Hz DisplayPort monitor; DSC support required for maximum video performance; Supports MST Pass-through
- ✓ **UNIVERSAL COMPATIBILITY:** TAA-Compliant KVM Switch works with any operating system including Windows, macOS, ChromeOS, and Linux; Compatible with all hardware platforms such as Intel and AMD; Supports ultrawide resolutions up to 5120x1440 60Hz
- ✓ **MULTIPLE SWITCHING OPTIONS:** Fast Switching via push-buttons or hotkeys with an audible buzzer providing confirmation; LEDs provide quick visual port selection status; Listen to audio from one computer while controlling the other
- ✓ **THOUGHTFUL DESIGN:** Metal housing is durable and helps prevent Electro-magnetic Interference (EMI); Overcurrent Protection (OCP) prevents peripherals from overdrawing power, reducing the risk of damage to the KVM and attached USB devices
- ✓ **TECHNICAL SPECIFICATIONS:** KVM Switch is DisplayPort 1.4 compliant, supporting resolutions up to 8K 60Hz or 4K 144Hz, HDR10, HDCP 2.2/1.4, and DSC; Supports DisplayPort Audio and 3.5mm analog audio; USB 5Gbps Hub Ports; OS Independent



Aprašymas

Share a mouse, keyboard, USB 5Gbps Hub, and 8K 60Hz DisplayPort between two DisplayPort enabled computers

Share and switch between two USB-A and DisplayPort-enabled computers, using this DisplayPort KVM Switch. Share an 8K 60Hz DisplayPort monitor, a keyboard and mouse, two USB 5Gbps devices, and two additional USB 2.0 devices.

High-Resolution 8K 60Hz Video

This KVM supports resolutions up to 8K 60Hz or 4K 144Hz/120Hz. Daisy chain additional monitors via MST pass-through. The KVM supports ultrawide resolutions of up to 5120x1440 at 60Hz. Ideal for applications such as CAD/CAM, video editing, and content creation. Support for High Dynamic Range (HDR) offers increased contrast, brightness, colors, and greater luminosity.

Customizable Switching

This Universal KVM Switch provides various switching options, including hotkey or push-button switching. Hotkeys allow for independent switching of audio and video, enabling audio playback from one computer while controlling the other. An audible buzzer confirms hotkey input, and LEDs provide a visual status of the selected host.

Universal Compatibility

The TAA-Compliant KVM Switch offers universal compatibility, working with all operating systems, including Windows, macOS, ChromeOS, and Linux. It is also compatible with all hardware platforms, including Intel and AMD.

Reliable Performance

The durable metal housing helps prevent Electro-magnetic Interference (EMI). Overcurrent Protection (OCP) ensures peripherals don't overdraw power, reducing the occurrence of device dropouts or shutdowns.

Techninė specifikacija

Ports & interfaces	
Number of computers controlled	2
Keyboard port type	USB
Mouse port type	USB
Video port type	DisplayPort
Console ports	3.5mm headphone, DisplayPort, USB A
DisplayPorts quantity	2
DisplayPort version	1.4
USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity	2
Console USB ports quantity	6
Console DisplayPorts ports quantity	1
Audio connections	Yes
Headphone outputs	3
DC-in jack	Yes

Performance	
HD type	8K Ultra HD
Maximum resolution	7680 x 4320 pixels
Data transfer rate (max)	5 Gbit/s
Scan interval	3,8,15,30 s
High Dynamic Range (HDR) supported	Yes
HDCP	Yes
Plug and Play	Yes
Daisy chain	No
Chipset	GL-3523
HDCP version	1.4/2.2
Design	
Rack mounting	No
Product colour	Black
Housing material	Steel
LED indicators	Yes
Push button	Yes
Hot keys	Yes
Mean time between failures (MTBF)	130000 h
Display	
Built-in display	No
On Screen Display (OSD)	No
Power	
Power source	DC
Input voltage	100 - 240 V
Input current	1 A
Output voltage	12 V
Output current	3 A
Power consumption (typical)	36 W
Compatible power plug types	EU, JP, UK, US
Sustainability	
Compliance certificates	CE, RoHS, Trade Agreements Act (TAA)
Sustainability compliance	Yes
Operational conditions	

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Weight & dimensions	
Width	100 mm
Depth	160 mm
Height	40 mm
Weight	600 g
Packaging data	
Package width	187 mm
Package depth	242 mm
Package height	93 mm
Package weight	1 kg
Packaging content	
Quick installation guide	Yes
Rubber feet	Yes
Logistics data	
Master (outer) case width	397 mm
Master (outer) case length	257 mm
Master (outer) case height	300 mm
Products per master (outer) case	60 pc(s)
Other features	
IP control	No
Matmenys ir svoris	
Matmenys (I × P × A)	24,00cm × 19,00cm × 9,00cm

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London,
CA

startech.com

ATSAKINGAS ASMUO ES

StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL
startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt