

# DELL PowerEdge T360 server 960 GB Tower (4.5U) Intel Xeon 6 6357P 3 GHz 64 GB DDR5-SDRAM 700 W

Gamintojas: **DELL** · Modelis: **6YVRW** · EAN: **5397184960479** · Prekės kodas: **948528**



## 8 772,90 €

Kaina su PVM

Be PVM: **7 250,33 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ No OS
- ✓ Intel Xeon 6 6357P (24MB Cache, 3GHz)
- ✓ 64GB DDR5-SDRAM (2 x 32) & 960GB SSD
- ✓ iDRAC9, Enterprise 16G



## Aprašymas

## Processing performance, GPU support

The 4.5U, single-socket PowerEdge T360 is a specially designed form factor for customers desiring versatility, affordability, and processing power.

## Techninė specifikacija

### Processor

|                        |              |
|------------------------|--------------|
| Processor family       | Intel Xeon 6 |
| Processor manufacturer | Intel        |

|                                            |            |
|--------------------------------------------|------------|
| Processor model                            | 6357P      |
| Processor frequency                        | 3 GHz      |
| Processor boost frequency                  | 5.4 GHz    |
| Performance cores                          | 8          |
| Processor cache                            | 24 MB      |
| Number of processors installed             | 1          |
| Thermal Design Power (TDP)                 | 80 W       |
| System bus rate                            | 16 GT/s    |
| Processor threads                          | 16         |
| Memory types supported by processor        | DDR5-SDRAM |
| Memory clock speeds supported by processor | 4800 MHz   |

### Memory

|                              |                           |
|------------------------------|---------------------------|
| Internal memory              | 64 GB                     |
| Internal memory type         | DDR5-SDRAM                |
| Maximum internal memory      | 128 GB                    |
| Buffered memory type         | Unregistered (unbuffered) |
| Memory slots                 | 4x DIMM                   |
| ECC                          | Yes                       |
| Memory layout (slots x size) | 2 x 32 GB                 |
| Memory data transfer rate    | 5600 MT/s                 |

### Storage

|                                |                      |
|--------------------------------|----------------------|
| Total storage capacity         | 960 GB               |
| RAID support                   | No                   |
| Optical drive type             | No                   |
| Number of SSDs installed       | 2                    |
| SSD capacity                   | 480 GB               |
| SSD interface                  | SATA III             |
| SSD size                       | 2.5"                 |
| Supported SSD sizes            | 3.5"                 |
| Number of SSDs supported       | 8                    |
| Supported RAID controllers     | PERC H755 Adapter FH |
| Hot-Plug support               | Yes                  |
| Storage drive adapter included | Yes                  |
| Storage drive adapter type     | 2.5" - 3.5"          |

### Network

|                                                 |                                                                                                                                     |
|-------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| LAN controller                                  | Broadcom 5720                                                                                                                       |
| Ethernet LAN                                    | Yes                                                                                                                                 |
| Cabling technology                              | 10/100/1000Base-T(X)                                                                                                                |
| Ethernet interface type                         | Gigabit Ethernet                                                                                                                    |
| <b>Ports &amp; interfaces</b>                   |                                                                                                                                     |
| Ethernet LAN (RJ-45) ports                      | 2                                                                                                                                   |
| USB 2.0 ports quantity                          | 3                                                                                                                                   |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 4                                                                                                                                   |
| VGA (D-Sub) ports quantity                      | 1                                                                                                                                   |
| Serial ports quantity                           | 1                                                                                                                                   |
| Power cables quantity                           | 2                                                                                                                                   |
| <b>Expansion slots</b>                          |                                                                                                                                     |
| PCI Express x4 slots                            | 2                                                                                                                                   |
| <b>Design</b>                                   |                                                                                                                                     |
| Chassis type                                    | Tower (4.5U)                                                                                                                        |
| Product colour                                  | Black                                                                                                                               |
| Bezel                                           | Yes                                                                                                                                 |
| <b>Performance</b>                              |                                                                                                                                     |
| Remote administration                           | iDRAC9, Enterprise 16G                                                                                                              |
| <b>Software</b>                                 |                                                                                                                                     |
| Operating system installed                      | No                                                                                                                                  |
| Compatible operating systems                    | Canonical Ubuntu Server LTS Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESXi |
| <b>Power</b>                                    |                                                                                                                                     |
| Redundant power supply (RPS) support            | No                                                                                                                                  |
| Power supply                                    | 700 W                                                                                                                               |
| Number of main power supplies                   | 1                                                                                                                                   |
| Power supply input voltage                      | 200 - 240 V                                                                                                                         |
| Power cable length                              | 2 m                                                                                                                                 |
| Power cable connector 1                         | C13 coupler                                                                                                                         |
| Power cable connector 2                         | C14 coupler                                                                                                                         |
| Power cable current                             | 10 A                                                                                                                                |
| <b>Operational conditions</b>                   |                                                                                                                                     |
| Storage temperature (T-T)                       | -40 - 65 °C                                                                                                                         |

|                                                         |                             |
|---------------------------------------------------------|-----------------------------|
| Storage relative humidity (H-H)                         | 5 - 95%                     |
| Operating altitude                                      | 0 - 2048 m                  |
| Non-operating altitude                                  | 0 - 12000 m                 |
| Certificates                                            |                             |
| 80 PLUS certification                                   | 80 PLUS Titanium            |
| Carbon footprint                                        |                             |
| Total carbon footprint (kg of CO2e)                     | 1409                        |
| Total carbon emissions, standard deviation (kg of CO2e) | 1213                        |
| Carbon emissions, manufacturing (kg of CO2e)            | 295.89                      |
| Carbon emissions, logistics (kg of CO2e)                | 154.99                      |
| Carbon emissions, energy usage (kg of CO2e)             | 929.94                      |
| Carbon emissions, end-of-life (kg of CO2e)              | 28.18                       |
| PAIA version                                            | 1.4.0, 2024                 |
| Weight & dimensions                                     |                             |
| Width                                                   | 175 mm                      |
| Depth                                                   | 581.1 mm                    |
| Other features                                          |                             |
| Data transfer rate                                      | 6 Gbit/s                    |
| Bytes per sector                                        | 512                         |
| Target workload                                         | Read Intensive (RI)         |
| Matmenys ir svoris                                      |                             |
| Matmenys (I × P × A)                                    | 56,00cm × 80,00cm × 40,00cm |

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Atitikties deklaracija](#)

Gamintojo ir saugos informacija

GAMINTOJAS  
DELL

ATSAKINGAS ASMUO ES  
Dell B.V.  
Transformatorweg 383, 1014 AK Amsterdam, NL  
[dell.com](#)

PLATINTOJAS  
MB KOMPIUTERIŲ GURU  
V. Nagevičiaus g. 3, LT-08237 Vilnius  
[info@shopro.lt](#)

Saugos dokumentai

- › [Atitikties deklaracija](#)