



**Mainboard  
ASROCK Intel  
B860 Express  
LGA1851 ATX  
Memory DDR5  
Memory slots 4  
1xPCI-Express  
4.0 16x 1xPCI-  
Express 5.0 16x  
1xM.2 1xHDMI  
1xAudio-Out  
1xMicrophone  
6xUSB 2.0  
6xUSB 3.2  
1xUSB-C  
w/Thunderbolt  
1xOptical S/PDIF  
1xRJ45  
B860LIVEMIXERWIFI**

Modelis: B860 LIVEMIXER WIFI

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

Gamintojas: ASROCK

EAN: 4711581490147

Prekės kodas: 94971

---

# 186.99€

---

## LIVE MIX. LIFE MAX

LiveMixer is designed through current-gen content creators, who need motherboards with great connectivity for streaming and other auxiliary devices. Also, its reliable performance allows us to provide wonderful contents and budget our time.

## Multiple Streaming Devices

We tested many video capture devices with different interfaces in order to provide the most stable system for content creators.

- GC553
- GC573
- Bu113
- GC311
- GC570D
- GC570
- HD60 S+

## Performance

### Optimized VRM Design

### 20K Capacitor

### Exclusive 20K Cap with 1000uF Capacitance

The upgraded 20K Black capacitor not only extends the lifespan to 20,000 hours but also increases the capacitance value from 560uF to 1000uF, bringing several benefits:

- Higher Capacitance: Greater charge storage for better support under high loads.

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

- Lower Ripple: Reduced power output fluctuations, improving quality.
- More Stable Output Current: Stable power supply, minimizing voltage impacts.
- Better Performance & System Stability: Increased reliability and consistent performance.

## **VRM Design**

### **12+1+1 Power Phase Design**

Featuring sturdy components and completely smooth power delivery to the CPU. Plus, it offers unmatched overclocking capabilities and enhanced performance with the lowest temperature for advanced gamers as well.

## **Dr. MOS**

Dr.MOS is the integrated power stage solution which is optimized for synchronous buck-set down voltage applications! Compared to traditional discrete MOSFETs, it intelligently delivers higher current for each phase, thus providing improved thermal result and superior performance.

## **Power Connector**

### **Hi-Density Power Connector**

CPU overclocking requires higher current. ASRock Hi-Density Power Connectors are designed to withstand higher currents compared to traditional CPU and ATX power connectors, providing a more stable system and reducing the risk of fire during heavy overclocking.

## **DDR5 XMP & EXPO Support**

Derived from the “built for stable and reliable” designing concept, ASRock does not compromise on any details. This motherboard is built with high quality materials, enthusiasts are able to enjoy the boost of DDR5 memory overclocking performance by enabling the pre-tested profiles. Make sure the memory modules are Intel® XMP/AMD EXPO™ capable and overclocking can be made so affordable, satisfying and absolutely no sweat at all.

## **High Speed M.2 Solution**

### **PCIe Gen5 Blazing M.2**

The Blazing M.2 accommodates the latest PCI Express 5.0 standard to perform twice the bandwidth compared to previous generation, with a breathtaking 128Gb/s transfer speed, it is ready to unleash the full potential of future ultrafast SSDs.

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

## **Hyper M.2 Gen4 x4**

Supports PCI Express 4.0 M.2 SSDs, it is capable of perform twice the speed compared to previous 3rd generation, giving a lightning fast data transferring experience.

## **DIY Friendly Design**

### **Graphics Card Lite Release**

Equipped with an enlarged latch for easy pressing, simplifying both the installation and removal of graphics cards.

## **M.2 Heatsink Toolless Design**

Besides the M.2 SSD toolless design on the motherboard, ASRock up a notch by introducing this industry first M.2 heatsink quick release mechanism on the motherboard. The user friendly toolless design helps installing M.2 SSD super easy & simple.

## **M.2 Bottom Heatsink**

The M.2 bottom heatsink is able to dissipate heat of the M.2 SSD efficiently through the motherboard PCB, maximize performance while maintaining system stability.

## **Enlarged M.2 Heatsink**

### **XXL M.2 Heatsink**

The extra large aluminum alloy M.2 heatsink effectively improves heat dissipation to keep those high speed M.2 SSDs as cool as possible, it is able to give better stability while maintaining top performance.

## **Anti-Drop Screw**

### **Tired of dropping screws or screws missing inside chassis?**

The enhanced M.2 heatsink with anti-drop screw design that make sure installation process more easily.

## **Cooling**

### **Intelligent Cooling Design**

#### **Aluminum Heatsink**

The first thing that catches the eye is the optimized Aluminum Heatsink Design. Heatsinks are

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

crucial for efficient heat dissipation, especially during heavy workloads like gaming or productivity tasks. Motherboard that built with heatsinks can effectively manage thermal performance, hence ensure system stability and durability effortlessly.

### **PWM/DC Fan Support**

ASRock fan headers automatically detect whether fans are running in DC or PWM mode, allowing users to fine-tune the fan curve and achieve quieter operation.

### **Thermistor Header**

The thermistor cable and thermistor header provide an additional source for temperature monitoring, offering customized thermal management solutions based on workload. Thermal management settings can be easily configured via Fan-Tastic Tuning or UEFI.

### **Fan-Tastic Tuning**

ASRock A-Tuning Fan-Tastic Tuning function enables users to auto-detect the minimum duty of each fan with a single click. Users can also easily adjust the fan curve via the visualized UI interface, meeting their system's cooling performance and noise reduction requirements.

### **Connectivity**

#### **Up to 22 USB Ports (Front + Rear)**

Featuring 22 USB ports, this design maximizes connectivity and provides more reliable and stable support for multiple auxiliary devices compared to external USB hubs.

#### **Wi-Fi 6E 802.11ax**

WiFi 6E technology has extended to the whole new 6GHz spectrum band, providing more WiFi capability and giving an even better and faster internet traffic. In addition to deliver higher speeds, the WiFi 6E also enhances the lower latency and supports service levels that are equivalent to 5G networks.

#### **Thunderbolt™ 4 Type-C**

Thunderbolt™ 4 technology brings speed and versatility to the most advanced USB Type-C, offering a fast and simple level of connection for work or home. It enables lightning-fast data transfer up to 40Gbps and connects external monitors, Thunderbolt™, and USB devices with a single Thunderbolt 4

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

cable.

## **Dragon 2.5 Gb/s LAN**

The intelligent 2.5Gb/s LAN platform is built for maximum networking performance for the demanding requirements of home networking, content creators, online gamers and high-quality streaming media. Boost networking performance up to 2.5X the bandwidth compared to the standard gigabit Ethernet, you'll enjoy the faster and uncompromised connectivity experience for gaming, file transfers and backups.

## **More than USB Transfer Speed**

### **Ultra USB Power**

Provides stable power and better sound experience! Ultra USB Power provides 5V power transformed from +12V power rail, whose voltage drop will be much lower than the +5V from the PSU under heavy loading, and prevents noise from other devices or RGB LED.

## **Nahimic Audio**

### **Audio That Matters**

Whether you are using headphones, a headset, external or internal speakers, via USB, Wi-Fi, analog output or even HDMI, Nahimic Audio offers you the most engaging listening experience, vibrant and rich with details.

## **Enhance Communication Quality**

The Powerful algorithms to ensure the best noise-free conversation, giving a constant vocal level no matter the distance from your mic. The Nahimic audio engine dynamically clear the sound and remove interference noise and lower the voice variation. Result is a better comprehension and less fatigue.

- Static Noise Suppression
- Echo Cancellation
- Lateral Sound Cancellation
- Voice Stabilizer

## **Ultimate Gaming Experience**

- Sound Tracker

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

The Sound Tracker is a visual indicator that points out the directions from which predominant sounds are coming. Each sound is properly positioned in 360° on a radar for a full immersion during the game.

- Works on any devices!

Enjoy the vibrant and high-quality Surround Sound on all your favorite audio devices. Nahimic is compatible with all of your favorite audio tools and ensures the best sound with any of them. Nahimic measure and improve to optimize our technology and offer you the best experience.

## **Stylish Design**

### **POLYCHROME RGB**

This motherboard features onboard RGB headers and addressable RGB headers that allow motherboard to be connected to compatible LED devices such as strip, CPU fans, coolers, chassis and so on. Users may also synchronize RGB LED devices across the Polychrome RGB Sync-certified accessories to create their own unique lighting effects.

### **SignalRGB**

SignalRGB unifies your RGB devices, offering seamless customization, game-reactive effects, macro automation, and system monitoring. The official partnership empowers ASRock motherboards with advanced lighting control, enhances compatibility with a diverse range of RGB devices, and provides greater customization flexibility.

## **DIY Friendly**

### **Customized Thermal Management**

The thermistor cable and thermistor header provide an additional source for temperature monitoring, offering customized thermal management solutions.

## **EZ Setting**

### **Auto Driver Installer**

No need to worry about lack of disk drive! Asrock preinstall LAN driver to ensure that you are able to install all drivers needed in an easier way than using SCD.

## **BIOS Flashback**

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

Get the most convenient BIOS flashing with just a simple click. Users can easily achieve the latest BIOS support with a USB and a power supply. No CPU, RAM or other components are required.

### **Flexible Integrated I/O Shield**

Unlike most so called pre-mounted I/O shield that is only decorated with fancy color schemes. We reserve more tolerance space and allow IO shield is adjustable when installing, thus fitting chassis perfectly without any mechanical issue.

- Supports Intel® Core™ Ultra Processors (Series 2) (LGA1851)
- 12+1+1+1+1 Power Phase, Dr.MOS for VCore+GT+SA
- 4 x DDR5 DIMMs, Supports Dual Channel, up to 8666+ (OC)
- 1 PCIe 5.0 x16, 1 PCIe 4.0 x16
- Graphics Output Options: 1 HDMI, 1 Thunderbolt™ 4 Type-C
- Realtek ALC1220 7.1 CH HD Audio Codec, Nahimic Audio
- 4 SATA3, 1 Blazing M.2 (PCIe Gen5x4), 2 Hyper M.2 (PCIe Gen4x4)
- 1 Thunderbolt™ 4 Type-C (Rear), 1 USB 3.2 Gen1 Type-C (Front), 10 USB 3.2 Gen1 (6 Rear, 4 Front), 10 USB 2.0 (6 Rear, 4 Front)
- Realtek 2.5G LAN
- 802.11ax Wi-Fi 6E + Bluetooth

Summary: Asrock B860 LiveMixer WiFi. Processor manufacturer: Intel, Processor socket: LGA 1851 (Socket V1), Compatible processor series: Intel Core Ultra (Series 2). Supported memory types: DDR5-SDRAM, Maximum internal memory: 256 GB, Memory slots type: DIMM. Supported storage drive interfaces: PCI Express 4.0, PCI Express 5.0, SATA III, Supported storage drive types: HDD & SSD, RAID levels: 0, 1, 5, 10. Maximum resolution: 7680 x 4320 pixels. USB connector type: USB Type-A, USB Type-C | Vendor Homepage:

<https://www.asrock.com/MB/Intel/B860%20LiveMixer%20WiFi/index.asp> | Audio chip: Realtek ALC1220 | Audio output channels: 7.1 | Certification: FCC, CE, ErP/EuP | Component for: PC | Motherboard chipset: Intel B860 | Motherboard chipset family: Intel | Motherboard form factor: ATX | Product colour: Black | Windows operating systems supported: Windows 11 x64 | Compatible processor series: Intel Core Ultra (Series 2) | Processor manufacturer: Intel | Processor socket: LGA 1851 (Socket V1) | Supported processor sockets: LGA 1851 | ECC compatibility: Non-ECC | Maximum internal memory: 256 | Memory channels: Dual-channel | Memory slots type: DIMM | Number of memory slots: 4 | Supported memory types: DDR5-SDRAM | Unbuffered memory: Yes | Number of

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

storage drives supported: 7 | RAID levels: 0/1/10/5 | RAID support: Yes | Supported storage drive interfaces: PCI Express 4.0,PCI Express 5.0,SATA III | Supported storage drive types: HDD & SSD | HDCP: Yes | Maximum resolution: 7680 x 4320 | Parallel processing technology support: Not supported | 12V power connector: Yes | ATX Power connector (24-pin): Yes | CPU fan connector: Yes | EPS power connector (8-pin): Yes | Front panel audio connector: Yes | Number of chassis fan connectors: 5 | Number of CPU fan connectors: 2 | Number of EPS power connectors (8-pin): 2 | Number of RGB LED pin headers: 1 | Number of SATA III connectors: 4 | Number of water pump connectors: 1 | RGB LED pin header: Yes | TPM connector: Yes | USB 2.0 connectors: 2 | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 3 | Ethernet LAN (RJ-45) ports: 1 | HDMI ports quantity: 1 | HDMI version: 2.1 | Headphone outputs: 1 | Microphone in: Yes | S/PDIF out port: Yes | Thunderbolt ports quantity: 1 | USB 2.0 ports quantity: 6 | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 6 | USB connector type: USB Type-A/USB Type-C | WiFi-AP antenna jack: 2 | Bluetooth: Yes | Bluetooth version: 5.3 | Ethernet interface type: 2.5 Gigabit Ethernet | Ethernet LAN: Yes | LAN controller: Dragon RTL8125BG | Top Wi-Fi standard: Wi-Fi 6E (802.11ax) | Wi-Fi: Yes | Wi-Fi standards: 802.11a/802.11b/802.11g/Wi-Fi 4 (802.11n)/Wi-Fi 5 (802.11ac)/Wi-Fi 6 (802.11ax)/Wi-Fi 6E (802.11ax) | 1st M.2 highest PCI Express generation: 5.0 | 1st M.2 largest key size: 2280 | 2nd M.2 highest PCI Express generation: 4.0 | 2nd M.2 largest key size: 2280 | 3rd M.2 highest PCI Express generation: 4.0 | 3rd M.2 largest key size: 2280 | Number of M.2 (M) slots: 3 | PCI Express x16 (Gen 4.x) slots: 1 | PCI Express x16 (Gen 5.x) slots: 1 | BIOS memory size: 256 | BIOS type: UEFI AMI | Depth: 244 | Width: 305 | Antenna included: Yes | Cables included: SATA | Model: B860 LiveMixer WiFi | Units per Shipping Box: 5 | Unit Calculated Volume: 0.008784 | Unit Calculated Weight: 2.18

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903