LogiLink CQM095S networking cable Green 10 m Cat6a S/FTP (S-STP)

Gamintojas: **LOGILINK** · Modelis: **CQM095S** · EAN: **4052792070620** · Prekės kodas: **950717**



32,90 €

Kaina su PVM

Be PVM: **27,19 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ M12 Industrial Ethernet cable, X-coded
- ✓ M12 connector straight - RJ45 connector straight
- ✓ Shielded flexible PUR cable, S/FTP, 26/19AWG
- ✓ Cat.6A Class EA channel (ISO/IEC 11801)
- ✓ M12 X-coding for 10 Gbit/s (IEC 61076-2-109)
- ✓ Suitable for drag chain (2 PfG 2577/08.16)
- ✓ Oil & UV resistance (EN 60811-2-1, IEC 60068-2-5)
- ✓ Ant-acid resistance, hydrolysis resistance
- ✓ Extended operation temperature: -40 to +90 °C
- ✓ Support PoE IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt





Aprašymas

M12 CAT6A Industrial Patch Cable, PUR, M12 X-coded to RJ45, 10 m" from LogiLink Professional
High quality connection cable for secure, high performance data transmission in industrial production. This drag chain compatible patch cable provides network connectivity for components with M12 connectors. It is ideal for increased mechanical stress in harsh environments and industrial applications. The weatherproof cable is oil, UV, acid, temperature and hydrolysis resistant, halogen free and flame retardant.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Techninė specifikacija

Features	
Cable length	10 m
Cable standard	Cat6a
Cable shielding	S/FTP (S-STP)
Connector 1	RJ-45
Connector 2	RJ-45
Product colour	Green
Connector 1 gender	Male
Connector 2 gender	Male
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Networking standards	IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt
AWG wire size	26/19
Data transfer rate	10000 Mbit/s
Frequency	500 MHz
Operational conditions	
Operating temperature (T-T)	-40 - 90 °C
Sustainability	
Doesn't contain	Halogen

Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

2direct GmbH
Langenstück 5, 58579 Schalksmühle, DE
info@2direct.de
2direct.de

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt