

Fujitsu PRIMERGY RX2540 M7 server 0 GB Rack (2U) Intel® Xeon® Gold 6426Y 2.5 GHz 32 GB DDR5-SDRAM 900 W

Gamintojas: FUJITSU · Modelis: VFY:R2547SC310IN · EAN: 4065221940067 · Prekės kodas: 950879



5 618,90 €

Kaina su PVM

Be PVM: 4 643,72 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ No OS
- ✓ 32GB (4800MHz) DDR5-SDRAM (1 x 32)
- ✓ Intel Xeon Gold 6426Y (37.5MB Cache, 2.5GHz)



Aprašymas

Unmatched Scalability and Performance

2U, 2-socket platform that provides scalability and performance to adapt to a variety of applications. Drive demanding workloads by latest 4th Generation Intel® Xeon® Scalable Processors with up to 60 cores per CPU.

Accelerate IT Transformation

Transform your data center for modern operations and drive demanding workloads with 32 DIMM modules (up to 8 TB). DDR5 DIMM memory provides fast, high capacity for memory intensive workloads.

Extensive Expandability

Maximize storage performance with up to 12x 3.5" or up to 24x 2.5" storage devices and ensure application performance scales to meet demands. Up to 8 PCIe 5.0 slots and OCP v3 adapters also ensure enough growth opportunities.

Agile Infrastructure Management

As you scale your infrastructure, scale your profitability with embedded intelligence from iRMC S6 as well as Infrastructure Manager (ISM) which enables organizations to have centralized control over the infrastructure using a single user interface.

Techninė specifikacija

Processor	
Processor family	Intel® Xeon® Gold
Processor manufacturer	Intel
Processor model	6426Y
Processor frequency	2.5 GHz
Processor boost frequency	4.1 GHz
Processor cores	16
Processor cache	37.5 MB
Motherboard chipset	Intel C741
Number of processors installed	1
Memory	
Internal memory	32 GB
Internal memory type	DDR5-SDRAM
Maximum internal memory	8 TB
Memory clock speed	4800 MHz
Memory layout (slots x size)	1 x 32 GB
Storage	
Total storage capacity	0 GB
RAID support	Yes
Optical drive type	No
HDD size	2.5"
Number of HDDs supported	16
Network	
Ethernet LAN	Yes
Ethernet interface type	Gigabit Ethernet
Ports & interfaces	

USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	6
VGA (D-Sub) ports quantity	1
Expansion slots	
PCI Express x16 (Gen 4.x) slots	1
Design	
Chassis type	Rack (2U)
Product colour	Black
Redundant fans support	Yes
Performance	
Trusted Platform Module (TPM)	Yes
Trusted Platform Module (TPM) version	2
Software	
Operating system installed	No
Compatible operating systems	Windows Server 2022 Datacenter Windows Server 2022 Standard Windows Server 2019 Datacenter Windows Server 2019 Standard Windows Server 2019 Essentials SUSE® Linux Enterprise Server 15 Red Hat® Enterprise Linux 8
Power	
Redundant power supply (RPS) support	Yes
Power supply	900 W
Number of redundant power supplies supported	2
Number of redundant power supplies installed	2
Power supply input voltage	100 - 240 V
Power supply input frequency	50/60 Hz
Weight & dimensions	
Width	482.2 mm
Depth	800 mm
Height	86.9 mm
Weight	32 kg
Matmenys ir svoris	
Svoris	28,50kg

Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

Fujitsu Limited

Kamikodanaka 4-1-1, 211-8588 Kanagawa, JP
global.fujitsu

ATSAKINGAS ASMUO ES

Fujitsu Germany GmbH

Mies-van-der-Rohe-Straße 8, 80807 München, DE
fujitsu.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt