LogiLink NMC002 network media converter 2500 Mbit/s Black

Gamintojas: **LOGILINK** · Modelis: **NMC002** · EAN: **4052792075571** · Prekės kodas: **950998**

37,90 €

Kaina su PVM

Be PVM: **31,32 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 2.5G to SFP Standalone Media Converter
- ✓ 1x 10/100/1000/2500 Mbps RJ45
- ✓ 1x 2.5GBASE-X SFP
- ✓ Supports full-duplex flow control
- ✓ Supports auto MDI/MDIX for TX port
- ✓ Suitable for singlemode or multimode fiber
- ✓ External power adapter 5V/1A

Aprašymas

The LogiLink Standalone Media Converter seamlessly converts electrical Ethernet signals to optical signals, enabling direct connections between copper and fiber optic cables. It is ideal for extending network reach, supporting distances of up to 20 kilometers over fiber and ensuring high availability and flexibility in the network architecture. The converter is ideal for integrating legacy networks with new cabling or overcoming length limitations.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Techninė specifikacija

Network	
Maximum data transfer rate	2500 Mbit/s
Networking standards	IEEE 802.3, IEEE 802.3i, IEEE 802.3u, IEEE 802.3az, IEEE 802.3x, IEEE 802.3z
Ethernet interface type	Fast Ethernet, Gigabit Ethernet, 2.5 Gigabit Ethernet
Ethernet LAN data rates	10,100,1000,2500 Mbit/s
Data transfer rate	2500 Mbit/s
Features	
Internal	No
LED indicators	Yes
Product colour	Black
Housing material	Metal
Ports & interfaces	
Fiber optic connector	SFP
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
DC-in jack	Yes
Power	
Input voltage	5 V
Input current	1 A
Power consumption (max)	2 W
External power adapter	Yes
Weight & dimensions	
Width	93.5 mm
Depth	70.5 mm
Height	26 mm
Weight	146 g
Operational conditions	
Operating temperature (T-T)	0 - 55 °C
Operating relative humidity (H-H)	20 - 80%
Packaging content	
AC adapter included	Yes
Manual	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Packaging data	
Package width	103 mm
Package depth	80 mm
Package height	60 mm
Package weight	244 g
Package type	Box

Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

2direct GmbH
Langenstück 5, 58579 Schalksmühle, DE
info@2direct.de
2direct.de

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt