

Lindy 150m Cat.6 4x4 HDMI 4K60 HDBaseT Matrix Extender

Gamintojas: **LINDY** · Modelis: **38345** · EAN: **4002888383455** · Prekės kodas: **951515**



1 505,91 €

Kaina su PVM

Be PVM: **1 244,55 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ HDBaseT Matrix Extender that extends and distributes HDMI, IR and RS-232 signals to 4 displays at distances of up to 150m
- ✓ Supports resolutions up to 4K60Hz with HDR
- ✓ Features loop-through HDMI outputs for local monitoring
- ✓ Supports power over Cable (PoC), EDID management, downscaler and Audio de-embedding functions
- ✓ 2 year warranty



Aprašymas

The Lindy 150m Cat.6 4x4 HDMI 4K60 HDBaseT Matrix Extender is an high-end and complete solution to switch and extend 4 HDMI signals to 4 HDBaseT receivers using Cat.6 or above cables up to 150m.

Supporting resolutions up to 4K60Hz including HDR and 1080p, the Matrix Extender is designed for use in Pro AV and digital signage applications for a variety of settings such as education, retail, immersive displays at events and conference rooms.

It supports several signals and features such as analog and coax de-embedded audio, IR matrix function and RS-232 control or pass-through signals. An advanced EDID management allow the user to select different EDID modes while the integrated HDMI loop-out ports enables simultaneous viewing so that a local display can be connected for monitoring each HDBaseT output, or to create additional viewing zones.

PoC (Power over Cable) functionality allows power to be supplied alongside data through Cat.6 network cable between the transmitter and any HDBaseT receiver, meaning only the transmitter unit needs to be powered on.

This unit can be managed by pushing the buttons on the front panel via OSD menu with a OLED screen, IR remote control (included), RS-232 or TCP/IP commands and web GUI.

Techninė specifikacija

Features	
Type	AV transmitter & receiver
Maximum resolution	3840 x 2160 pixels
Cable types supported	Cat6
Maximum transfer distance	150 m
High Dynamic Range (HDR) supported	Yes
EDID management	Yes
HDCP pass-through	Yes
Infrared (IR) frequency range	20 - 60 kHz
Supported video modes	1080p
Bandwidth	18 Gbit/s
Audio formats supported	LPCM
On/off switch	Yes
HDCP	Yes
Material	Metal
Signal-to-Noise Ratio (SNR)	90 dB
HDCP version	2.2
Product colour	Black
Certification	California Proposition 65
Ports & interfaces	
Connectivity technology	Wired
RJ-45 output ports	4
HDBaseT port	Yes
HDMI in	4
Number of HDMI outputs	5
HDMI version	2

RS-232 input ports	2
Digital audio coaxial out	4
Audio (L/R) out	4
3.5 mm (1/8-inch) in	Yes
3.5 mm (1/8-inch) out	Yes
Audio RCA outputs	4
Power	
Power source type	AC
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power requirements	60 W
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 90%
Weight & dimensions	
Width	440 mm
Depth	200 mm
Height	45 mm
Weight	5.31 kg
Receiver dimensions (WxDxH)	140 x 65 x 18 mm
Packaging data	
Package width	510 mm
Package depth	401 mm
Package height	98 mm
Package weight	6.33 kg
Package type	Box
Packaging content	
Manual	Yes
Packaging content	4x4 HDBaseT Extender Matrix - Transmitter 4 x HDBaseT Receivers 5 x IR Emitter Cable, 1.5m 5 x IR Receiver Cable, 1.5m 10 x Mounting Ears & Screws 4 x 3-Pin Terminal Block 4 x 5-Pin Terminal Block RS-232 Male to Female cable, 1.5m 4 x mains cables (EU, UK, US & AUS), 1.5m Lindy Manual
Technical details	
Warranty period	2 year(s)

Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS, UKCA
Sustainability compliance	Yes

Dokumentai ir vaizdo įrašai

› [Naudojimo instrukcija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

LINDY International Ltd.

Sadler Forster Way Unit 103, TS17 9JY Stockton-on-Tees, GB
lindy.com

ATSAKINGAS ASMUO ES

LINDY-Elektronik GmbH

Markircher Str. 22, 68229 Mannheim, DE
lindy.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt