# Lindy 3m USB 3.0 Active Extension Slim

Gamintojas: **LINDY** · Modelis: **43400** · EAN: **4002888434003** · Prekės kodas: **951516**



**35.90€**

Kaina su PVM

Be PVM: **29.67€**

**In Stock**

**Prekė internetu**
Nuskenuokite kodą arba apsilankykite www.shopro.lt

## Pagrindinės savybės

- ✓ USB 3.0 Active Extension Repeater Lead
- ✓ Supports transfer rates up to 5Gbps
- ✓ For even greater distances simply connect up to 5 cables in series
- ✓ USB Power Adapter cable included






## Aprašymas

The Lindy USB 3.0 Active Extension Cable uses built-in active electronics to extend the cable length of a USB 3.0 device by an additional 3m whilst continuing to support data transfer rates of up to 5Gbps. With its USB A male and USB A female connector it allows Type A devices such as storage devices, webcams and other Type A devices to be connected at longer distances to PCs, laptops and tablets, while also ensuring flexible positioning.

Up to 5 of these USB 3.0 Active Extensions Slim can be chained together. In addition, a maximum of 5 of the different cable lengths of these USB 3.0 Active Extensions Slim can be combined with each other. The only exception is the 15m version No. 43404: as it has 2 chipsets, a maximum of 3 other USB 3.0 Active Extensions Slim can be combined with it.

The Lindy USB 3.0 Active Extension Slim is supplied with power via the USB bus, but also has a DC socket for connecting a power supply unit for devices with high power requirements or if you want to connect several cables in series.

The Lindy USB 3.0 Active Extension Cable is compatible with all USB Type A equipped computers. The cable's unique and slim design allows installation in narrow surroundings - an advantage over other active USB leads which use bulky connectors. With plug and play functionality, this extension cable can be installed quickly and with minimum fuss, ideal for both professional and first time users.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

## Information about USB 3.0, 3.1 & 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.
USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps.
USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

### Techninė specifikacija

| | |
|---|---|
| **Ports & interfaces** | |
| Ports quantity | 2 |
| Host interface | USB 3.2 Gen 1 (3.1 Gen 1) Type-C |
| Hub interfaces | USB 3.2 Gen 1 (3.1 Gen 1) Type-C |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity | 1 |
| **Features** | |
| Data transfer rate | 5000 Mbit/s |
| Product colour | Black |
| Housing material | Acrylonitrile butadiene styrene (ABS) |
| LED indicators | Yes |
| Cable type | Round cable |
| AWG wire size | 26 |
| Cable jacket material | Polyvinyl chloride (PVC) |
| Cable length | 3 m |
| Cable diameter | 6.5 mm |
| Conductor material | Tinned copper |
| Connector contacts plating | Nickel |
| Plug and Play | Yes |
| Transmission medium | Twisted pair |
| Certification | CE, FCC, RoHS & REACH, CP65 |
| **Power** | |
| Power supply type | DC |
| **Weight & dimensions** | |
| Weight | 260 g |
| Connector 1 dimensions (WxDxH) | 41.1 x 16.5 x 9.5 mm |
| Connector 2 dimensions (WxDxH) | 67.5 x 22 x 13.5 mm |
| **Packaging data** | |
| Quantity per pack | 1 pc(s) |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

| | |
|---|---|
| Package width | 236 mm |
| Package depth | 255 mm |
| Package weight | 300 g |
| Package type | Polybag |
| **Packaging content** | |
| Manual | Yes |
| Quick start guide | Yes |
| **Operational conditions** | |
| Minimum operating temperature | 0 °C |
| Maximum operating temperature | 40 °C |
| Operating temperature (T-T) | 0 - 40 °C |
| Operating temperature (T-T) | 32 - 104 °F |
| Storage temperature (T-T) | -10 - 60 °C |
| **Technical details** | |
| Compliance certificates | CE, Federal Communications Commission (FCC), REACH, RoHS |
| **Matmenys ir svoris** | |
| Svoris | 0.25kg |

## Dokumentai ir vaizdo įrašai

- Product leaflet
- CE marking

## Gamintojo ir saugos informacija

MANUFACTURER

**LINDY International Ltd.**
Sadler Forster Way Unit 103, TS17 9JY Stockton-on-Tees, GB
lindy.com

EU RESPONSIBLE PERSON

**LINDY-Elektronik GmbH**
Markircher Str. 22, 68229 Mannheim, DE
lindy.com

DISTRIBUTOR

**MB KOMPIUTERIŲ GURU**
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

### Saugos dokumentai

- CE marking