# Vertiv Avocent 32-Port ACS 8000 with dual AC Power Supply and Analog Modem - ACS8032MDAC-404

Gamintojas: **VERTIV** · Modelis: **ACS8032MDAC-404** · EAN: **7612205057432** · Prekės kodas: **953667**




**4 849,90 €**

Kaina su PVM

Be PVM: **4 008,18 €**

**Sandėlyje**

**Prekė internetu**
Nuskenuokite kodą arba apsilankykite www.shopro.lt

## Pagrindinės savybės

- ✓ Secure in-band and out-of-band network remote management
- ✓ Fast, automated configuration with Zero Touch Provisioning
- ✓ Access and troubleshoot remote locations using automatic network failover
- ✓ No need for adaptors with automatic Cyclades™ and Cisco pin-out conversions
- ✓ Compliance with data center access and security policies
- ✓ Console event logging and notification
- ✓ Integrated support for 1Gb SFP fiber modules
- ✓ USB ports to support new IT equipment and external devices



## Aprašymas

The Avocent ACS 8000 advanced console server offers upgraded and advanced features, that deliver scalable and high-performance solutions for IT administrators. The console server features a dual ARM core processor platform with dual Gigabit Ethernet ports and dual Gigabit fiber ports for redundancy. In addition, there is a sensor port, to connect a variety of sensors for monitoring and logging on the appliance. The serial ports are auto sensing for pin-out and the Avocent ACS 8000 advanced console server also offers robust features to meet the requirements of the demanding data center management applications. Features combine automated discovery tools to ease identification of servers, routers, switches and power devices, connected to any serial port, saving time at initial configuration and installation. To comply with existing data center network access policy, the Avocent ACS 8000 advanced console server provides customizable, multiple access levels for secure management. The console servers provide

a complete solution for secure, remote control with advanced console server features, such as enhanced security, data logging and event monitoring. In addition, the Avocent ACS 8000 advanced console server supports network standards, such as Internet Protocol version 6 (IPv6).

## Techninė specifikacija

| | |
|---|---|
| **Technical details** | |
| Rack mounting | Yes |
| Internal modem | Yes |
| Zero Touch Provisioning (ZTP) | Yes |
| Web-based management | Yes |
| Temperature sensor | Yes |
| Product colour | Black |
| **Management features** | |
| Management protocols | CLI, HTTP/ HTTPS, SNMP |
| **Security** | |
| Authentication method | LOCAL,LDAP,RADIUS,TACACS+ and OneTimePasswords(OTP) |
| Security algorithms | 3DES, 128-bit AES, 192-bit AES, 256-bit AES, AES, FIPS 140-2, HTTPS, IPSec, SHA-256, SNMP, SNMPv3, SSH, SSH-2 |
| IP address filtering | Yes |
| One-time password (OTP) | Yes |
| **Ports & interfaces** | |
| Console port | RJ-45 |
| Serial ports quantity | 32 |
| USB 2.0 ports quantity | 8 |
| Ethernet LAN (RJ-45) ports | 2 |
| SFP module slots quantity | 2 |
| AC outlet types | C13 coupler |
| **Software** | |
| Operating system installed | Embedded LINUX |
| **Weight & dimensions** | |
| Dimensions (WxDxH) | 438.2 x 241.3 x 44.5 mm |
| Weight | 3.4 kg |
| **Power** | |
| Power source type | AC |
| AC input voltage | 106 - 240 V |
| AC input frequency | 50 - 60 Hz |

| | |
|---|---|
| Power consumption (typical) | 20 W |
| Power consumption (max) | 35 W |
| Input current | 0.1 A |
| Number of power supply units | 2 |
| **Operational conditions** | |
| Operating temperature (T-T) | -10 - 60 °C |
| Storage temperature (T-T) | -20 - 70 °C |
| Operating relative humidity (H-H) | 20 - 80% |
| Storage relative humidity (H-H) | 5 - 95% |
| **Certificates** | |
| Certification | FCC Class A, CE Class A (EU), ICES-003 (Canada), VCCI (Japan), RCM (Australia), Customs Union (CU), KCC (Korea), UL (USA), cUL (Canada), EN-60950 (EU), CB, Customs Union (CU) |
| **Memory** | |
| Flash memory | 16000 MB |
| RAM capacity | 1024 MB |
| RAM type | DDR3L |
| eMMC capacity | 16 GB |
| **Processor** | |
| Processor family | ARM Cortex-A9 |
| Processor architecture | ARM Cortex-A9 |
| Processor cores | 2 |
| Processor frequency | 667 MHz |
| **Network** | |
| Copper ethernet cabling technology | 10BASE-T, 100BASE-T, 1000BASE-T |
| Cable types supported | Cat5, Cat5e, Cat6, Cat6+, Cat6a, Cat6e, Cat7, Fiber |
| **Other features** | |
| Safety | UL (USA), cUL (Canada), EN-60950 (EU), CB, Customs Union (CU) |

## Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

## Gamintojo ir saugos informacija

GAMINTOJAS

**Vertiv**

ATSAKINGAS ASMUO ES

**Vertiv GmbH**
August-Everding-Str 25, 81671 München, DE
vertiv.com

PLATINTOJAS

**MB KOMPIUTERIŲ GURU**
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt