

StarTech.com 10GbE Open SFP+ Fiber Media Converter, Standalone 10 Gigabit Ethernet RJ-45 to 10GBASE-X SFP+, Single-Mode / Multi-Mode, 16K Jumbo Frames - TAA

Gamintojas: **STARTECH** · Modelis: **MCM10GSFP2** · EAN: **065030916844** · Prekės kodas: **954154**



312,91 €

Kaina su PVM

Be PVM: **258,60 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ **Upgrade Networks with Copper-to-Fiber Conversion**: Convert 10GBASE-T copper (RJ-45) to 10G fiber through an open SFP+ slot; Supports multi-mode or single-mode transceivers, for flexible deployment and extended reach
- ✓ **Flexible Mounting**: Use as a compact standalone unit or mount to a wall, rack, DIN rail (ADJINKIT) or chassis (MCM7-MEDIA-CHASSIS, MCM15-MEDIA-CHASSIS) for clean, professional integration into structured wiring closets, data centers, or server rooms
- ✓ **Reliable Performance at 10Gbps Speed**: Supporting 10GBASE-T, 10GBASE-X, Jumbo Frames (up to 16K), full-duplex flow control, and auto MDI/MDI-X; Plug-and-play operation across high-speed 10G network links
- ✓ **Deploy Efficiently in Compact, Power-Sensitive Spaces**: Consumes only 5.3W (typical) via 5V DC input from included power adapter or chassis power supply and rated for 0°C to 50°C operating environments; Does not support PoE
- ✓ **The IT Pro's Choice**: Designed for reliability in edge and on-prem deployments, our media converters are lab-tested and field-proven for seamless integration and maximum uptime; Backed by free lifetime multi-lingual technical assistance



Aprašymas

Connect a Gigabit copper network to a Gigabit fiber network using an SFP+ transceiver of your choice.

High-Speed Copper-to-Fiber Conversion

This compact 10G media converter enables seamless copper-to-fiber connectivity for high-speed network upgrades and extended reach. Featuring an open SFP+ slot, it converts 10GBASE-T (RJ-45) to 10G fiber and supports multi-mode or single-mode transceivers (e.g., 10GBASE-SR/LR) for flexible deployment across enterprise and telecom environments.

Versatile Mounting and Deployment

Ideal for structured wiring closets, server rooms, or remote network upgrades, the converter supports wall-mount, DIN rail, and chassis installations. It can operate as a standalone device or integrate into a media converter chassis system.

Optimized for 10Gbps Networks

Built for 10G speeds, the converter supports 16K Jumbo Frames, auto MDI/MDI-X, and full-duplex flow control. With plug-and-play setup and reliable diagnostics, it ensures consistent performance across 10G links.

Efficient, Compact Design

With low 5.3W (typical) power consumption via 5V DC input, this power-efficient converter operates in environments ranging from 0°C to 50°C. It avoids PoE-related conflicts and is ideal for compact, power-sensitive deployments.

Techninė specifikacija

Network	
Maximum data transfer rate	10000 Mbit/s
Converter input interface	10GBase-T
Converter output interface	10GBase-X
Networking standards	IEEE 802.3
Ethernet interface type	2.5 Gigabit Ethernet, 5 Gigabit Ethernet, 10 Gigabit Ethernet, Fast Ethernet, Gigabit Ethernet
Ethernet LAN data rates	100,1000,2500,5000,10000 Mbit/s
Jumbo frames support	Yes
Jumbo frames	16000
Flow control support	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Duplex system	Full
Performance	
Fiber mode structure	Multi-mode, Single-mode
Mean time between failures (MTBF)	50000 h

Features

Internal	No
Plug and Play	Yes
LED indicators	Activity, Link, Power
Product colour	Black

Ports & interfaces

Fiber optic connector	SFP+
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
DC-in jack	Yes

Power

Input voltage	100 - 240 V
Input current	0.4 A
Output voltage	5 V
Output current	2 A
External power adapter	Yes

Weight & dimensions

Width	93.5 mm
Depth	70 mm
Height	26 mm
Weight	216 g

Operational conditions

Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-10 - 70 °C
Operating relative humidity (H-H)	5 - 95%

Packaging content

AC adapter included	Yes
User guide	Yes

Packaging data

Package width	95 mm
Package depth	149 mm
Package height	92 mm
Package weight	398 g

Certificates

Compliance certificates	CE, Federal Communications Commission (FCC), RoHS, Trade Agreements Act (TAA)
-------------------------	---

Logistics data

Master (outer) case width	405 mm
Master (outer) case length	490 mm
Master (outer) case height	330 mm
Products per master (outer) case	20 pc(s)

Dokumentai ir vaizdo įrašai

- › Gaminio lankstinukas
- › Vaizdo įrašas youtube.com/watch?v=y3rXUbSIGW4

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London,
CA

startech.com

ATSAKINGAS ASMUO ES

StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL
startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt