StarTech.com DKT30CHVSDPD knyginių kompiuterių dokas / jungčių replikatorius Vielinis USB 3.2 Gen 1 (3.1 Gen 1) Type-C Pilka

Gamintojas: **STARTECH** · Modelis: **DKT30CHVSDPD** · EAN: **065030891769** · Prekės kodas: **954531**



51,90 €

Kaina su PVM

Be PVM: **42,89 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Vielinis
- ✓ Priimančioji sąsaja: USB 3.2 Gen 1 (3.1 Gen 1) Type-C
- ✓ „USB Power Delivery“
- ✓ Ethernet LAN jungtis 10,100,1000 Mbit/ai Wake-on-LAN pasirengimas
- ✓ Pilnai abipusis (duplex)
- ✓ MicroSD (TransFlash), SD, SDHC, SDXC







Aprašymas

USB-C Multiport Adapter | HDMI or VGA Video | 100W PD Pass-Through | 2-Port USB Hub (5Gbps) | SD/MicroSD Card Reader

This USB-C multiport adapter supports 4K 30Hz HDMI® or 1080p VGA and turns your MacBook Pro, Dell XPS, or other USB-C™ laptops or tablet into a workstation, anywhere you go. The USB Type-C multiport adapter provides 4K HDMI or 1080p VGA video output, two USB 3.1 Gen 1 Type-A (5Gbps) ports (including 1x Fast Charge port), a single USB 3.1 Gen 1 Type-C (5Gbps) port, an SD/MicroSD card reader and a Gigabit Ethernet port, all through one connection to your laptop's USB-C or Thunderbolt 3/4™ port. Plus, it offers advanced charging through USB Power Delivery 3.0 and an extra-long attached 12-inch (30 cm) host cable for an extended reach to offer more set up flexibility.

USB 3.1 Gen 1 (5Gbps) is also known as USB 3.2 Gen 1 (5Gbps) and USB 3.0 (5Gbps).

Enhance Productivity

The portable docking station offers versatile video flexibility by connecting your laptop to a 4K 30Hz HDMI monitor (4096 x 2160p) or a 1080p (60Hz) VGA monitor (1920x1080) to create a powerful workstation. For added video flexibility, the dock also supports ultra-wide monitors.

Connect Your Devices

The USB-C to USB 3.1 Gen 1 hub gives you two USB-A (5Gbps) ports and one USB-C (5Gpbs) port to connect your USB devices.

Built-In SD Card Reader

Access your multimedia content with ease. The multiport adapter provides direct access to your SD, SDHC™ and SDXC™ memory cards or microSD (uSD) cards.

Charge Your Laptop and Peripherals

With support for USB PD 3.0 (up to 100W), the USB Type-C multiport adapter lets you power and charge your laptop when a power adapter is connected to the USB-C power input port. Plus, one of the USB-A (5Gbps) ports supports BC 1.2 fast charge to power your peripherals when the dock is connected to a USB-C power adapter. PD 3.0 features Fast Role Swap to prevent USB, Ethernet and video disruption when you switch power sources (USB-C power adapter to bus power).

Reliable Network Connectivity

The Gigabit Ethernet port ensures reliable wired network access with support for PXE Boot and WoL.

Enhance Productivity and Device Management with the StarTech.com Connectivity Tools Application

Developed to improve performance and security, StarTech.com Connectivity Tools is the only software suite on the market that works with a wide range of IT connectivity accessories. The software suite includes:

-

Advanced Windows Layout Utility : To setup and save custom windows layouts.

-

Mac Address Pass-Through Utility : To improve network security.

-

USB Event Monitoring Utility : To track and log connected USB devices

-

Wi-Fi Auto Switch Utility : Enabling users to quickly access faster network speeds via wired LAN.

For more information and to download the StarTech.com Connectivity Tools application, please visit: www.StarTech.com/Connectivity-Tools

The DKT30CHVSDPD is backed by a StarTech.com 3-year warranty and free lifetime technical support.

The StarTech.com Advantage

Techninė specifikacija

Ryšys	
Ryšio technologija	Vielinis
Priimančioji sąsaja	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 2.0 portų kiekis	0
USB 3.2 (3.1 1 kart.) A tipo prievadų skaičius	2
HDMI portų kiekis	1
Mikrofonas, line-in jack	Ne
Ausinių išvestys	0
USB 3.2 (3.1 1 kart.) C tipo prievadų skaičius	2
„USB Power Delivery“	Taip
USB maitinimo šaltinio peržiūra	3.0
USB maitinimo tiekimas iki	100 W
VGA (D-Sub) portų kiekis	1
Tinklas	
Ethernet LAN jungtis	Taip
Ethernet LAN (RJ-45) portų kiekis	1
Eterneto LAN duomenų perdavimo norma	10,100,1000 Mbit/ai
Wake-on-LAN pasirengimas	Taip
Tinklo standartai	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u
Pilnai abipusis (duplex)	Taip
Veikimo charakteristikos	
Produkto spalva	Pilka
Integruotas kortelių skaitytuvas	Taip
Suderinamos atminties kortelės	MicroSD (TransFlash), SD, SDHC, SDXC
Duomenų perdavimo sparta	5 Gbit/s
HD tipas	4K Ultra HD
Maksimali skaitmeninė raiška	3840 x 2160 pikseliai
Maksimali analogo raiška	1920 x 1080 pikseliai
Palaikomų ekranų skaičius	1

Maksimalus atnaujinimo dažnis	60 Hz
LED indikatoriai	Aktyvumas, Greitis
UASP palaikymas	Taip
Energijos valdymas	
Energijos suvartojimas	15 W
Programinė įranga	
Palaikomos „Windows“ operacinės sistemos	Windows 7 Ultimate x64, Windows 10, Windows 7 x64, Windows 10 Education, Windows 8, Windows 10 Education x64, Windows 7, Windows 8 Enterprise, Windows 10 Enterprise, Windows 7 Enterprise, Windows 8 Enterprise x64, Windows 10 Enterprise x64, Windows 7 Enterprise x64, Windows 8 Pro, Windows 10 Home, Windows 7 Home Basic, Windows 8 Pro x64, Windows 10 Home x64, Windows 7 Home Basic x64, Windows 8 x64, Windows 10 IOT Core, Windows 7 Home Premium, Windows 8.1, Windows 10 IoT Enterprise, Windows 7 Home Premium x64, Windows 8.1 Enterprise, Windows 10 Pro, Windows 7 Professional, Windows 8.1 Enterprise x64, Windows 10 Pro x64, Windows 7 Professional x64, Windows 8.1 Pro, Windows 10 x64, Windows 7 Starter, Windows 8.1 Pro x64, Windows 11, Windows 7 Starter x64, Windows 8.1 x64, Windows 11 x64, Windows 7 Ultimate
Palaikomos MAC operacinės sistemos	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 13.0 Ventura
Kitos palaikomos operacinės sistemos	ChromeOS
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 45 °C
Sandėliavimo temperatūros norma (T-T)	-10 - 70 °C
Darbo santykinės drėgmės diapazonas	10 - 90%
Svoris ir matmenys	
Plotis	326 mm
Ilgis	59 mm
Aukštis	14 mm
Svoris	137 g
Pakuotės duomenys	
Pakuotės plotis	110 mm
Pakuotės gylis	59 mm
Pakuotės aukštis	15 mm
Pakuotės turinys	
Greitos pradžios vadovas	Taip
Techninė informacija	
Atitikties sertifikatai	CE, RoHS

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Logistikos duomenys	
Gaminių skaičius pagrindinėje (išorinėje) dėžėje	30 vnt
Pagrindinės (išorinės) dėžės plotis	450 mm
Pagrindinės (išorinės) dėžės ilgis	340 mm
Pagrindinės (išorinės) dėžės aukštis	200 mm
Darniosios sistemos (DS) kodas	84733020
Kitos savybės	
Kabelio ilgis	0,3 m
Lustų rinkinys	Realtek - RTL8153, Parade Technologies - PS176, VIA Tech - VL102, VIA Tech - VL817
Matmenys ir svoris	
Matmenys (I × P × A)	17,00cm × 14,00cm × 3,00cm
Svoris	0,17kg

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.
Artisans Crescent 45, N5V 5E9 Ontario, London, CA
startech.com

ATSAKINGAS ASMUO ES

StarTech.com Limited
Laarderhoogtweg 25, 1101 EB Amsterdam, NL
startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt