

LevelOne 155Mbps Single-mode BIDI SFP Transceiver, 20km, TX 1550nm / RX 1310nm

Gamintojas: **LEVEL ONE** · Modelis: **SFP-7331** · EAN: **4015867154748** · Prekės kodas: **955488**



36,91 €

Kaina su PVM

Be PVM: **30,50 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ SFP Fiber optic 155 Mbit/s
- ✓ Hot-swap
- ✓ Input voltage: 3.3 V



Aprašymas

The LevelOne SFP-7331 is a high performance, cost-effective SFP transceiver. It provides up to 155Mbps bi-directional data transfer rate at distances up to 20km on a single fiber core. These bi-directional SFP Transceivers allow data transfer in either direction through a single optical fiber by employing separate wavelengths travelling in either direction.

The SFP-7331 transmits using a wavelength of 1550nm and receives using a wavelength of 1310nm. When coupled with the LevelOne SFP-7321 transceiver which transmits at and receives at the opposite rates (1550nm TX and 1310nm RX) you get bi-direction data communication on a single fiber core.

- 1550nm FP LD
- Data Rate: 125~155Mbps, NRZ
- Single +3.3V Power Supply
- RoHS Compliant and Lead-free

- AC/AC Differential Electrical Interface
- Compliant with Multi-Source Agreement(MSA)
- Compliant with SFF-8472 Digital Diagnostic Monitoring Interface
- Single LC Connector
- Compliance with specifications for IEEE802.3ah 100BASE-BX10-U
- Compliance with FDDI PMD Standard
- Compliance with ATM Standard

Techninė specifikacija

Performance	
SFP transceiver type	Fiber optic
Maximum data transfer rate	155 Mbit/s
Interface type	SFP
Single-mode fiber (SMF) supported	Yes
Fiber optic connector	LC
Fiber cable diameters supported (core/cladding)	9/125 µm
Maximum transfer distance	20 m
Tx power (min)	-14 dBmW
Tx power (max)	-8 dBmW
Networking standards	IEEE 802.3ah
Fiber ports quantity	1
Features	
Hot-swap	Yes
Power	
Input voltage	3.3 V
Maximum voltage	6 V
Maximum current	0.3 A
Certificates	
Compliance certificates	RoHS
Safety	EN 60825-1
Certification	CE, FCC
Operational conditions	
Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	5 - 95%
Weight & dimensions	

Width	13.7 mm
Depth	56.5 mm
Height	8.95 mm
Weight	20 g
Packaging content	
Quantity per pack	1 pc(s)
Packaging data	
Package width	75 mm
Package depth	51 mm
Package height	130 mm
Package weight	60 g
Logistics data	
Harmonized System (HS) code	85369010
Matmenys ir svoris	
Svoris	0,06kg

Gamintojo ir saugos informacija

GAMINTOJAS
LevelOne

ATSAKINGAS ASMUO ES
Digital Data Communications GmbH
Im Defdahl 10 F, 44141 Dortmund, DE
level1.com

PLATINTOJAS
MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt