LevelOne 1.25Gbps Single-mode SFP Transceiver, 10km, 1310nm

Gamintojas: **LEVEL ONE** · Modelis: **GVT-0301** · EAN: **4015867224397** · Prekės kodas: **955490**



38,90 €

Kaina su PVM

Be PVM: **32,15 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ SFP Fiber optic 1250 Mbit/s
- ✓ Wavelength: 1310 nm
- ✓ Hot-Plug support
- ✓ Input voltage: 3.5 V





Aprašymas

Product Overview

The LevelOne GVT-0301 SFP (Small form-factor pluggable) Transceiver provide flexibility for utilizing fiber Gigabit network connections in both data and telecommunication applications.

Support for Mini GBIC Connectivity

GVT-0301 SFP Transceiver Series transceivers support LX standard optic with single-mode mini GBIC connectors. They provide signal amplification to transfer and receive data between two ends of mini GBIC ports.

Multi-Purpose Usage

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

GVT-0301 SFP transceivers can be used for distributed multi-processing, switch-to-switch interfaces, high-speed I/O file transfer, bus extension applications, and for a channel extender or data storage applications.
The LevelOne GVT-0301 can be used in any LevelOne switch or modules that support SFP modules.

- Add a 1000Base-LX connection to LevelOne switchs with mini GBIC/SFP ports
- Connect switches up to 10km away with each other
- TTL signal detect indicator
- Compliant with IEEE802.3z Gigabit Ethernet
- Easy to install and hot-swappable
- Differential LVPECL input and output
- Single 3.3V power supply
- Duplex LC connector

Techninė specifikacija

Performance	
SFP transceiver type	Fiber optic
Maximum data transfer rate	1250 Mbit/s
Interface type	SFP
Single-mode fiber (SMF) supported	Yes
Fiber optic connector	LC
Fiber cable diameters supported (core/cladding)	9/125 µm
SFP transceiver standard	LX
Maximum transfer distance	10000 m
Wavelength	1310 nm
Tx power (min)	-9.5 dBmW
Tx power (max)	-3 dBmW
Link budget	10.5 dB
Networking standards	IEEE 802.3z
Features	
Hot-Plug support	Yes
Compatible products	GSW-2453 GVT-4000
Power	
Input voltage	3.5 V
Maximum voltage	6 V
Maximum current	0.3 A
Certificates	
Certification	Class 1 Laser: EN60825-1 FDA 21: 1040.10, 1040.11
Operational conditions	

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Operating temperature (T-T)	0 - 70 °C
Operating relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	13.5 mm
Depth	55.5 mm
Height	8.5 mm
Packaging content	
Quantity per pack	1 pc(s)
Packaging data	
Package width	70 mm
Package depth	50 mm
Package height	130 mm
Package weight	70 g
Logistics data	
Harmonized System (HS) code	85369010
Country of origin	Taiwan

Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

LevelOne

ATSAKINGAS ASMUO ES

Digital Data Communications GmbH
Im Defdahl 10 F, 44141 Dortmund, DE
level1.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt