

Lindy 45583 networking cable Grey 2 m Cat6 S/FTP (S-STP)

Gamintojas: **LINDY** · Modelis: **45583** · EAN: **4002888455831** · Prekės kodas: **957289**



16,90 €

Kaina su PVM

Be PVM: **13,97 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Twisted Pair Patch Cable with RJ45 connectors and Test Report (100% Test)
- ✓ Cat.6 S/FTP PIMF, LSZH
- ✓ Integrated snagless connector for latch protection
- ✓ Gold plated pins for better conductivity and elimination of signal loss



Aprašymas

Cat.6 S/FTP network cable with support for bandwidth up to 250MHz and features a snagless design with gold plated contacts for ethernet standards up to 1GBase-T.

Cat.6 cable for operating frequencies up to 250MHz in shielded version with braid as overall shield and foil shield for the individual wire pairs (S/FTP). Cat.6 cables are widespread throughout the professional sector. They are ideal for Gigabit Ethernet or AV extension applications.

These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag. The 100% Component test slip included in each polybag ensures flawless compatibility between devices, each component of the cable is individually tested helping to eliminate problems such as insertion loss, return loss and crosstalk.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

The halogen-free sheath material of the LSZH cable makes the product suitable for use in public spaces with its low smoke emission and elimination of toxic halogen emissions.

Available lengths: 0.3m, 0.5m, 1m, 2m, 3m, 5m, 7.5m, 10m, 15m, 20m, 30m, 40m, 50m, 60m, 70m, 80m, 90m, 100m.

Available colours: Black, Blue, Gray, Red.

Techninė specifikacija

Features	
Cable length	2 m
Cable standard	Cat6
Cable shielding	S/FTP (S-STP)
Connector 1	RJ-45
Connector 2	RJ-45
Product colour	Grey
Connector 1 gender	Male
Connector 2 gender	Male
Connector contacts plating	Nickel/Gold
Connector shielding	Yes
Connector shield material	Aluminium/Polyester
Jacket material	Low smoke zero halogen (LSZH)
Conductor material	Copper
Cable class	E
Cabling technology	10/100/1000Base-T(X)
AWG wire size	26
Frequency	250 MHz
Bend radius (min)	1.86 cm
Operational conditions	
Operating temperature (T-T)	-25 - 60 °C
Storage temperature (T-T)	-25 - 60 °C
Sustainability	
Doesn't contain	Halogen
Certificates	
Certification	RoHS, REACH, UL
Weight & dimensions	
Outer diameter	6.2 mm
Connector 1 dimensions (WxDxH)	11.6 x 21.5 x 8.3 mm
Connector 2 dimensions (WxDxH)	11.6 x 21.5 x 8.3 mm
Packaging data	
Package type	Polybag

Other features

Category6

Logistics data

Harmonized System (HS) code84733080

Gamintojo ir saugos informacija

GAMINTOJAS

LINDY International Ltd.

Sadler Forster Way Unit 103, TS17 9JY Stockton-on-Tees, GB

lindy.com

ATSAKINGAS ASMUO ES

LINDY-Elektronik GmbH

Markircher Str. 22, 68229 Mannheim, DE

lindy.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt