

Lindy 5m Cat.6A S/FTP LSZH Network Cable, Grey

Gamintojas: **LINDY** · Modelis: **47136** · EAN: **4002888471367** · Prekės kodas: **957290**



13,90 €

Kaina su PVM

Be PVM: **11,49 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Twisted Pair Patch Cable with RJ45 connectors
- ✓ Cat.6A S/FTP PIMF, LSZH
- ✓ Integrated snagless connector for latch protection
- ✓ Gold plated pins for better conductivity and elimination of signal loss



Aprašymas

Cat.6A S/FTP network cable with support for bandwidth up to 500MHz and features a snagless design with gold plated contacts for ethernet standards up to 10 GBase-T.

Cat.6A cable, shielded with braid as overall shield and foil shield for the individual wire pairs (S/FTP). Cat.6A cables meet the requirements of 10 Gigabit Ethernet (10GBaseT) with an operating frequency of up to 500MHz. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

The halogen-free sheath material of the LSZH cable makes the product suitable for use in public spaces with its low smoke emission and elimination of toxic halogen emissions.

Available lengths: 0.3m, 0.5m, 1m, 1.5m, 2m, 3m, 5m, 7.5m, 10m, 15m, 20m, 30m.

Available colours: Black, Blue, Grey, Red, White

Techninė specifikacija

Features	
Cable length	5 m
Cable standard	Cat6a
Cable shielding	S/FTP (S-STP)
Connector 1	RJ-45
Connector 2	RJ-45
Product colour	Grey
Connector 1 gender	Male
Connector 2 gender	Male
Connector contacts plating	Nickel/Gold
Connector shielding	Yes
Connector shield material	Aluminium
Jacket material	Low smoke zero halogen (LSZH)
Conductor material	Copper
Cable class	Ea
Cabling technology	10/100/1000Base-T(X)
AWG wire size	27
Data transfer rate	1000 Mbit/s
Frequency	500 MHz
Bend radius (min)	7.2 cm
Plug and Play	Yes
Nominal attenuation	49.3dB/100m @ 500MHz
Operational conditions	
Operating temperature (T-T)	-10 - 60 °C
Storage temperature (T-T)	-20 - 75 °C
Certificates	
Certification	RoHS, REACH, UL
Weight & dimensions	
Outer diameter	6 mm
Connector 1 dimensions (WxDxH)	11.6 x 21.5 x 8.3 mm
Connector 2 dimensions (WxDxH)	11.6 x 21.5 x 8.3 mm
Packaging content	
Quantity per pack	1 pc(s)

Packaging data

Package type	Polybag
--------------	---------

Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------

Matmenys ir svoris

Svoris	0,19kg
--------	--------

Gamintojo ir saugos informacija

GAMINTOJAS

LINDY International Ltd.

Sadler Forster Way Unit 103, TS17 9JY Stockton-on-Tees, GB

[lindy.com](https://www.lindy.com)

ATSAKINGAS ASMUO ES

LINDY-Elektronik GmbH

Markircher Str. 22, 68229 Mannheim, DE

[lindy.com](https://www.lindy.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt