

Lindy 47544 networking cable White 5 m Cat6a U/FTP (STP)

Gamintojas: **LINDY** · Modelis: **47544** · EAN: **4002888475440** · Prekės kodas: **957305**



15,90 €

Kaina su PVM

Be PVM: **13,14 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Twisted Pair Patch Cable with RJ45 connectors
- ✓ Cat.6A U/FTP, Flat
- ✓ Integrated snagless connector for latch protection
- ✓ Gold plated pins for better conductivity and elimination of signal loss



Aprašymas

Cat.6A U/FTP flat network cable with support for bandwidth up to 500MHz and features a snagless design with gold plated contacts for ethernet standards up to 1GBase-T.

Cat.6A cable, for operating frequencies up to 500MHz, shielded with foil shielded with single pair shielding (U/FTP). Designed as flat ribbon cable for use in environments with restricted or limited installation space. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

The very flexible and thin ribbon cable construction allows the cables to be installed in restricted or limited spaces.

Available lengths: 0.3m, 1m, 2m, 3m, 5m, 10m.

Available colours: Black, White.

Techninė specifikacija

Features	
Cable length	5 m
Cable standard	Cat6a
Cable shielding	U/FTP (STP)
Connector 1	RJ-45
Connector 2	RJ-45
Product colour	White
Connector 1 gender	Male
Connector 2 gender	Male
Connector contacts plating	Nickel/Gold
Connector shielding	Yes
Connector shield material	Aluminium
Jacket material	Polyvinyl chloride (PVC)
Conductor material	Copper
Cabling technology	10/100/1000Base-T(X)
AWG wire size	32
Frequency	500 MHz
Bend radius (min)	6 cm
Operational conditions	
Operating temperature (T-T)	-10 - 60 °C
Storage temperature (T-T)	-10 - 40 °C
Certificates	
Certification	RoHS, REACH, California Proposition 65
Weight & dimensions	
Connector 1 dimensions (WxDxH)	11 x 28 x 6 mm
Connector 2 dimensions (WxDxH)	11 x 28 x 6 mm
Packaging data	
Package type	Polybag
Logistics data	
Harmonized System (HS) code	84733080
Matmenys ir svoris	
Svoris	0,11kg

Gamintojo ir saugos informacija

GAMINTOJAS

LINDY International Ltd.

Sadler Forster Way Unit 103, TS17 9JY Stockton-on-Tees, GB

lindy.com

ATSAKINGAS ASMUO ES

LINDY-Elektronik GmbH

Markircher Str. 22, 68229 Mannheim, DE

lindy.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt