

Lindy 47635 networking cable Grey 5 m Cat6a S/FTP (S-STP)

Gamintojas: **LINDY** · Modelis: **47635** · EAN: **4002888476355** · Prekės kodas: **957308**



15,90 €

Kaina su PVM

Be PVM: **13,14 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Twisted Pair Patch Cable with RJ45 connectors
- ✓ Cat.6A S/FTP PIMF, TPE
- ✓ Integrated snagless connector for latch protection
- ✓ Gold plated pins for better conductivity and elimination of signal loss



Aprašymas

Cat.6A S/FTP network cable with support for bandwidth up to 500MHz and features a snagless design with gold plated contacts for ethernet standards up to 10 GBase-T. The TPE Jacket is a non-toxic alternative to PVC allowing it to be used in a variety of environments, as well as being more flexible than its counterpart with a flex rating of 10 million it has high impact and tear resistance making it a very durable jacket material. Cat.6A cable, shielded with braid as overall shield and foil shield for the individual wire pairs (S/FTP). Cat.6A cables meet the requirements of 10 Gigabit Ethernet (10GBaseT) with an operating frequency of up to 500MHz. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

The TPE used as a sheath material provides increased flexibility and easy handling of cables.

Available lengths: 0.3m, 0.5m, 1m, 1.5m, 2m, 3m, 5m, 7.5m, 10m, 15m, 20m, 30m.

Techninė specifikacija

Features	
Cable length	5 m
Cable standard	Cat6a
Cable shielding	S/FTP (S-STP)
Connector 1	RJ-45
Connector 2	RJ-45
Product colour	Grey
Connector 1 gender	Male
Connector 2 gender	Male
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Nickel/Gold
Connector shielding	Yes
Connector shield material	Aluminium
Jacket material	Thermoplastic elastomer (TPE)
Cable shape	Round
Conductor material	Copper
Connector housing material	Polycarbonate (PC)
Cabling technology	10GBase-T
AWG wire size	28
Frequency	500 MHz
Bend radius (min)	7.4 cm
Snagless cable boot	Yes
Plug and Play	Yes
Operational conditions	
Operating temperature (T-T)	-10 - 60 °C
Storage temperature (T-T)	-20 - 75 °C
Certificates	
Compliance certificates	REACH, RoHS
Certification	RoHS, REACH, California Proposition 65
Weight & dimensions	
Width	11.6 mm
Depth	22.8 mm

Height	8.3 mm
Outer diameter	6.2 mm
Connector 1 dimensions (WxDxH)	11.6 x 22.8 x 8.3 mm
Connector 2 dimensions (WxDxH)	11.6 x 22.8 x 8.3 mm
Packaging content	
Quantity per pack	1 pc(s)
Packaging data	
Package type	Polybag
Logistics data	
Quantity per box	1 pc(s)
Warranty period	10 year(s)
Technical details	
Sustainability compliance	Yes

Gamintojo ir saugos informacija

GAMINTOJAS	ATSAKINGAS ASMUO ES	PLATINTOJAS
LINDY International Ltd.	LINDY-Elektronik GmbH	MB KOMPIUTERIŲ GURU
Sadler Forster Way Unit 103, TS17 9JY Stockton-on-Tees, GB	Markircher Str. 22, 68229 Mannheim, DE	V. Nagevičiaus g. 3, LT-08237 Vilnius
lindy.com	lindy.com	info@shopro.lt