

LevelOne 1.25Gbps Multi-mode SFP Transceiver, 2km, 1310nm

Gamintojas: **LEVEL ONE** · Modelis: **SFP-3111** · EAN: **4015867154670** · Prekės kodas: **957386**



36,91 €

Kaina su PVM

Be PVM: **30,50 €**

Sandėlyje



Prekė internetu

Nuskuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ SFP Fiber optic 1250 Mbit/s
- ✓ Wavelength: 1310 nm
- ✓ Hot-swap
- ✓ Input voltage: 3.3 V



Aprašymas

LevelOne SFP-3111 is a high performance and cost-effective multi-mode SFP transceiver. Intended for use with Gigabit Ethernet, it provides up to 1.25 Gbps bi-directional data transfer rate on a single duplex fiber core. For use with 50 and 62.5 micron fiber cables, it can reach a distance of up to 2km. The SFP-3111 transceiver operates using a wavelength of 1310nm with a FP LD Laser Diode light source and has a LC connector.

- 1310nm FP LD
- Data Rate: 1.25Gbps, NRZ
- Single +3.3V Power Supply
- RoHS Compliant and Lead-free
- AC/AC Differential Electrical Interface
- Compliant with Multi-Source Agreement (MSA)
- Small Form Factor Pluggable (SFP)
- Duplex LC Connector
- Compliance with specifications for IEEE-802.3z Gigabit Ethernet at 1.25Gbps
- Compliance with ANSI specifications for Fiber Channel applications at 1.06Gbps

- No configuration or installation software required
- Eye Safety Designed to meet LASER Class 1 comply with EN60825-1

Techninė specifikacija

Performance	
SFP transceiver type	Fiber optic
Maximum data transfer rate	1250 Mbit/s
Interface type	SFP
Multi-mode fiber (MMF) supported	Yes
Fiber optic connector	LC
Fiber cable diameters supported (core/cladding)	62.5/125 µm
Maximum transfer distance	2000 m
Wavelength	1310 nm
Tx power (min)	-9.5 dBmW
Tx power (max)	1 dBmW
Networking standards	IEEE 802.3z
Duplex system	Full
Fiber ports quantity	1
Features	
Plug and Play	Yes
Hot-swap	Yes
Power	
Input voltage	3.3 V
Maximum voltage	6 V
Maximum current	0.3 A
Certificates	
Compliance certificates	RoHS
Safety	EN 60825-1
Certification	CE, FCC
Operational conditions	
Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	5 - 95%
Weight & dimensions	
Width	57 mm

Depth	12 mm
Height	13.7 mm
Weight	20 g
Packaging content	
Quantity per pack	1 pc(s)
Packaging data	
Package width	106 mm
Package depth	20 mm
Package height	65 mm
Package weight	35 g
Logistics data	
Harmonized System (HS) code	85369010
Matmenys ir svoris	
Svoris	0,04kg

Gamintojo ir saugos informacija

GAMINTOJAS

LevelOne

ATSAKINGAS ASMUO ES

Digital Data Communications GmbH
Im Defdahl 10 F, 44141 Dortmund, DE
level1.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt