

StarTech.com Multi-Mode (MM) / Single Mode (SM) Fiber Media Converter for 10/100/1000 Networks, Standalone Gigabit Ethernet to Fiber Converter, Open SFP Slot - TAA

Gamintojas: **STARTECH** · Modelis: **MCM1110SFP** · EAN: **065030861472** · Prekės kodas: **959216**



81,90 €

Kaina su PVM

Be PVM: **67,69 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ **EXTEND GIGABIT NETWORKS OVER LONG DISTANCES:** Convert RJ45 to fiber with full duplex performance, overcoming copper limits and resisting EMI; Link Fault Pass-through speeds up troubleshooting while ensuring reliable uptime for mission-critical deployments
- ✓ **FLEXIBLE CONFIGURATION:** Fiber media converter with open SFP slot which allows you to customize the network extension distance to your requirements with any MSA-compliant multi or single mode transceiver
- ✓ **AUTO NEGOTIATION:** Media converter features a 10/100/1000 Mbps compatible RJ45 port that supports auto negotiation to bridge different network devices/speeds to a Gigabit fiber network; Supports IEEE 802.1q Tag VLAN pass-through and 9K Jumbo Frames
- ✓ **COMPACT AND DURABLE:** Media converter installs almost anywhere with little to no configuration; Also mounts in the MCM7-MEDIA-CHASSIS or MCM15-MEDIA-CHASSIS for clean, professional integration into structured data centers, or server rooms; TAA compliant
- ✓ **THE IT PRO'S CHOICE:** Designed for reliability in edge and on-prem deployments, our media converters are lab-tested and field-proven for seamless integration and maximum uptime; Backed by free lifetime 24/5 multi-lingual technical assistance



Aprašymas

Convert and extend different networks over a Gigabit fiber cable connection using the SFP of your choice

This fiber media converter offers an easy, cost-effective way to extend your network over fiber, using the SFP of your choice. It converts a copper RJ45 Ethernet connection to Gigabit fiber to extend your network over longer distances or connect workstations to switches. The converter provides a powerful networking solution for campuses, businesses, government facilities, stadiums, or other areas requiring network access.

A cost-effective extension and flexible performance

The Gigabit fiber media converter provides a cost-efficient way to connect your Ethernet network to remote devices over a fiber backbone. It features an open SFP slot that lets you choose the MSA-compliant Gigabit SFP that best suits your fiber connection mode (single / multimode) and distance requirements.

A versatile way to connect different networks

Fully compatible with 10/100/1000Base-T Ethernet networks, the fiber media converter supports auto negotiation to bridge different speed networks and devices to a Gigabit fiber network. It provides versatile connectivity to your existing networks and devices, allowing you to maximize the usage and performance of legacy equipment.

Installation is fast and easy

The unmanaged fiber media converter has a standalone design with simple plug-and-play set-up to ensure fast and easy installation. Compact in size, the converter gives you flexible installation options - including a wall mounting option.

Techninė specifikacija

Network	
Maximum data transfer rate	1000 Mbit/s
Converter input interface	1000Base-T, 100Base-TX, 10Base-T
Converter output interface	1000Base-LX, 1000Base-SX
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3z
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Jumbo frames support	Yes
Auto MDI/MDI-X	Yes
Duplex system	Full
Performance	
Wavelength-division multiplexing (WDM)	Yes
Fiber mode structure	Multi-mode, Single-mode
Mean time between failures (MTBF)	50000 h
Features	
Internal	No

LED indicators	Activity, Link, Power
Product colour	Black
Housing material	Steel
Ports & interfaces	
Fiber optic connector	SFP
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
DC-in jack	Yes
Power	
Input voltage	100 - 240 V
Input current	1 A
Output voltage	5 V
Output current	2 A
Power consumption (typical)	5 W
Power over Ethernet (PoE)	No
External power adapter	Yes
Power plug type	Type N
Weight & dimensions	
Width	70 mm
Depth	95 mm
Height	26 mm
Weight	185 g
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-10 - 70 °C
Operating relative humidity (H-H)	5 - 95%
Packaging content	
Manual	Yes
Packaging data	
Package width	285 mm
Package depth	139 mm
Package height	69 mm
Package weight	544 g

Certificates	
Compliance certificates	RoHS
Certification	CE, FCC
Logistics data	
Harmonized System (HS) code	85176990
Master (outer) case width	590 mm
Master (outer) case length	370 mm
Master (outer) case height	311 mm
Products per master (outer) case	20 pc(s)

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

<div>GAMINTOJAS</div> <div>StarTech.com Ltd.</div> <div>Artisans Crescent 45, N5V 5E9 Ontario, London, CA</div> <div>startech.com</div>	<div>ATSAKINGAS ASMUO ES</div> <div>StarTech.com Limited</div> <div>Laarderhoogtweg 25, 1101 EB Amsterdam, NL</div> <div>startech.com</div>	<div>PLATINTOJAS</div> <div>MB KOMPIUTERIŲ GURU</div> <div>V. Nagevičiaus g. 3, LT-08237 Vilnius</div> <div>info@shopro.lt</div>
--	--	---