

StarTech.com Cisco GLC-LH-SMD Compatible SFP Module - 1000BASE-LH - 1GbE Single Mode Fiber SMF Optic Transceiver - 1GE Gigabit Ethernet SFP - LC 20km - 1310nm - DDM Cisco Firepower, IE2000, IE4000

Gamintojas: **STARTECH** · Modelis: **SFPG1320C** · EAN: **065030846677** · Prekės kodas: **959217**



74,90 €

Kaina su PVM

Be PVM: **61,90 €**

[Sandėlyje](#)



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 100% CISCO GLC-LH-SMD COMPATIBLE: Works with Cisco switches like Firepower, IE2000, IE4000, C9300, IE3000 and others
- ✓ TECHNICAL SPECS: 1000BASE-LH / 1 Gbps / Single Mode (SMF) / LC Connector / 1310nm / Digital Diagnostic Monitoring (DDM) / Distances up to 20km (12.4mi)
- ✓ TESTED FOR OEM HOST COMPATIBILITY: Hot-swappable in Cisco routers and switches; DDM support reports the transceiver's status to most SNMP network management tools
- ✓ WORKS WITH MSA COMPLIANT SWITCHES: Also works with switch models from Ubiquiti, D-Link, Netgear, Supermicro, TP-Link and more that accept uncoded modules
- ✓ THE IT PRO'S CHOICE: Designed and built for IT Professionals, this SFP module is backed for life (lifetime of module, not network switch), including free lifetime 24/5 multi-lingual technical assistance.



Aprašymas

1000 Mbps (1 Gbps) | Single Mode Fiber | LC | 20 km (12.4 mi) | Lifetime Warranty

The SFPG1320C is a Cisco GLC-LH-SMD compatible fiber transceiver module that has been designed, programmed and tested to work with Cisco® brand switches and routers. It delivers dependable 1 GbE connectivity over fiber cable, for 1000BASE-LH compliant networks, with a maximum distance of up to 20 km (12.4 mi).

Technical Specifications:

- Wavelength: 1310nm
- Maximum Data Transfer Rate: 1.25 Gbps
- Type: Single Mode Fiber
- Connection Type: LC Connector
- Maximum Transfer Distance: 20 km (12.4 mi)
- MTBF: 2,722,277 hours
- Power Consumption: Less than 1 Watt
- Digital Diagnostics Monitoring (DDM): Yes

This SFP fiber module is hot-swappable, making upgrades and replacements seamless by minimizing network disruptions.

StarTech.com SFPs

All StarTech.com SFP & SFP+ transceiver modules are backed by a lifetime warranty and free lifetime multilingual technical support. StarTech.com offers a wide variety of SFP modules and direct-attach SFP cables, providing the convenience and reliability you need to ensure dependable network performance.

Techninė specifikacija

Performance	
SFP transceiver type	Fiber optic
Maximum data transfer rate	1250 Mbit/s
Interface type	SFP
Single-mode fiber (SMF) supported	Yes
Multi-mode fiber (MMF) supported	No
Fiber optic connector	LC
SFP transceiver standard	LH
Maximum transfer distance	20000 m
Wavelength	1310 nm
Networking standards	IEEE 802.3z
Duplex system	Full, Half
Digital Diagnostics Monitoring (DDM)	Yes
Wavelength-division multiplexing (WDM)	No
Features	

Product colour	Silver
Hot-swap	Yes
Mean time between failures (MTBF)	2722277 h
Brand compatibility	Cisco
Compatible products	GLC-LH-SMD
Power	
Power consumption (typical)	1 W
Certificates	
Compliance certificates	RoHS
Certification	CE, FCC, UL, REACH
Operational conditions	
Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	30 - 70%
Weight & dimensions	
Width	12 mm
Depth	60 mm
Height	10 mm
Weight	20 g
Packaging content	
Quantity per pack	1 pc(s)
Packaging data	
Package width	91 mm
Package depth	113 mm
Package height	33 mm
Package weight	48 g
Logistics data	
Master (outer) case width	254 mm
Master (outer) case length	302 mm
Harmonized System (HS) code	85369010
Master (outer) case height	201 mm
Products per master (outer) case	36 pc(s)

Dokumentai ir vaizdo įrašai

> [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London,
CA

startech.com

ATSAKINGAS ASMUO ES

StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL
startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt