

Intellinet 10GBase-T to 10GBase-R Media Converter, 1 x 10 GB SFP+ Slot, 1 x 10GB RJ45 Port

Gamintojas: INTELLINET · Modelis: 508193 · EAN: 766623508193 · Prekės kodas: 959257



262,90 €

Kaina su PVM

Be PVM: 217,27 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ One 10 GB RJ45 port — maximum distance of 100 m (300 ft.)
- ✓ One 10 GB SFP+ port
- ✓ Supports IEEE802.3u, 10GBase-T and 10GBase-FL
- ✓ Supports full-duplex mode or half-duplex mode operation with autonegotiation
- ✓ Status LEDs for power and Link/TX for both ports
- ✓ External 12 VDC power adapter
- ✓ Three-year warranty



Aprašymas

The Intellinet Network Solutions 10GBase-T to 10GBase-R Media Converter offers the network designer a device for migration from copper-based Ethernet to Fibre Ethernet. Now, migration or expansion of existing networks can be achieved with minimum cost and complexity. The converter is

completely transparent to the network, so the network performs exactly the way it did before, only now it can support both copper and Fibre media. And with a super-fast 10 Gbps connection, network speed stays constant for high-bandwidth data transfers.

Expand The size of an existing network.

The 10GBase-T to 10GBase-R Media Converter Provides fibre connectivity to Ethernet segments, allowing for even greater networking expansion between extended workgroups. It also provides building-to-building connectivity without the need for the cost and disruption associated with the installation of additional routers.

Enhance the distance between networking devices.

Connecting the converter to fibre segments further extends distances between network nodes, offering increased spatial and distance options for networks where none existed before.

Cabling Flexibility

Network managers can install fibre cabling anywhere within a network without changing the arrangement of their copper-based Ethernet. The compact size of the converter allows it to be easily deployed in any narrow desktop location or to be used in a wall-mount installation. Several converters can be simultaneously installed into a 19"; rackmountable chassis, providing much-needed flexibility for networks.

Techninė specifikacija

Network	
Maximum data transfer rate	10000 Mbit/s
Networking standards	IEEE 802.3u
Ethernet interface type	10 Gigabit Ethernet
Ethernet LAN data rates	10,100,1000,1200,2500,5000,10000 Mbit/s
Auto-negotiation	Yes
Duplex system	Full, Half
Performance	
Maximum transfer distance	100 m
Features	
Internal	No
LED indicators	Activity, Link
Product colour	Black
Housing material	Metal
Ports & interfaces	
Fiber optic connector	SFP+
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1

Power

Input voltage	12 V
Input current	0.5 A
Power consumption (max)	5 W
External power adapter	Yes

Weight & dimensions

Width	70 mm
Depth	95 mm
Height	25 mm
Weight	200 g

Operational conditions

Operating temperature (T-T)	0 - 55 °C
Storage temperature (T-T)	-10 - 70 °C
Operating relative humidity (H-H)	5 - 80%

Packaging content

Manual	Yes
--------	-----

Logistics data

Harmonized System (HS) code	85176990
-----------------------------	----------

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

IC Intracom Vertriebs GmbH

Löhbacher Str. 7, D-58553 Halver, DE
[intellinetnetwork.eu](mailto:info@shopro.lt)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt