

StarTech.com HPE J8177C Compatible SFP Module - 1000BASE-T - SFP to RJ45 Cat6/Cat5e - 1GE Gigabit Ethernet SFP - RJ-45 100m - HPE 1810, 1820, 2530

Gamintojas: **STARTECH** · Modelis: **J8177CST** · EAN: **065030865234** · Prekės kodas: **959300**



54,90 €

Kaina su PVM

Be PVM: **45,37 €**

[Sandėlyje](#)



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ **100% HPE J8177C COMPATIBLE:** Works with HPE switches like 1810, 1820, 2530, 2610, 2620 and others
- ✓ **TECHNICAL SPECS:** 1000BASE-T / 1Gbps / Copper / RJ-45 Connector / Distances up to 100m (328ft)
- ✓ **TESTED FOR OEM HOST COMPATIBILITY:** Hot-swappable in HPE routers and switches
- ✓ **WORKS WITH MSA COMPLIANT SWITCHES:** Also works with switch models from Ubiquiti, D-Link, Netgear, Supermicro, TP-Link and more that accept uncoded modules
- ✓ **THE IT PRO'S CHOICE:** Designed and built for IT Professionals, this SFP module is backed for life (lifetime of module, not network switch), including free lifetime 24/5 multi-lingual technical assistance



Aprašymas

1000 Mbps (1 Gbps) | Copper | RJ45 | 100 m (328 ft) | Lifetime Warranty

The J8177CST is an HPE J8177C compatible copper transceiver module that has been designed, programmed and tested to work with HPE® brand switches and routers. It delivers dependable 1 GbE connectivity over fiber cable, for 1000BASE-T compliant networks, with a maximum distance of

up to 100 m (328 ft).

Technical Specifications:

- Maximum Data Transfer Rate: 1000 Mbps
- Type: Copper
- Connection Type: RJ45 Connector
- Maximum Transfer Distance: 100 m (328 ft)
- MTBF: 4,655,371 hours
- Power Consumption: Less than 1.3 Watts
- Digital Diagnostics Monitoring (DDM): No

This SFP copper module is hot-swappable, making upgrades and replacements seamless by minimizing network disruptions.

StarTech.com SFPs

All StarTech.com SFP & SFP+ transceiver modules are backed by a lifetime warranty and free lifetime multilingual technical support. StarTech.com offers a wide variety of SFP modules and direct-attach SFP cables, providing the convenience and reliability you need to ensure dependable network performance.

Techninė specifikacija

Performance	
SFP transceiver type	Copper
Maximum data transfer rate	1000 Mbit/s
Interface type	SFP
Fiber optic connector	MiniGBIC
Maximum transfer distance	100 m
Networking standards	IEEE 802.3ab
Ethernet LAN (RJ-45) ports	1
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Digital Diagnostics Monitoring (DDM)	No
Features	
Product colour	Silver
Housing material	Aluminium
Hot-swap	Yes
Mean time between failures (MTBF)	4655371 h
Power	
Power consumption (typical)	1.3 W
Certificates	
Compliance certificates	RoHS

Certification	CE, FCC
Operational conditions	
Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	30 - 75%
Weight & dimensions	
Width	14 mm
Depth	68 mm
Height	14 mm
Weight	25 g
Packaging content	
Quantity per pack	1 pc(s)
Packaging data	
Package width	93 mm
Package depth	112 mm
Package height	33 mm
Package weight	53 g
Logistics data	
Master (outer) case width	355 mm
Master (outer) case length	410 mm
Harmonized System (HS) code	85369010
Master (outer) case height	340 mm
Products per master (outer) case	100 pc(s)
Country of origin	China

Dokumentai ir vaizdo įrašai

› [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London,
CA

startech.com

ATSAKINGAS ASMUO ES

StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL

startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt