

Intellinet Transceiver Module Optical, 10 Gigabit Fiber SFP+, 10GBase-SR (LC) Multi-Mode Port, 300m, Wavelength 850nm, Ethernet, Fibre, HPE Compliant, Equivalent to HPE J9150A / J9150D / JD092A / JD092B, Three Year Warranty

Gamintojas: **INTELLINET** · Modelis: **508766** · EAN: **766623508766** · Prekės kodas: **960489**



36,91 €

Kaina su PVM

Be PVM: **30,50 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Compatible with switches and routers from HPE (Hewlett Packard Enterprise)
- ✓ Data transfer rate: 10 Gbps
- ✓ One 10GBase-SR multi-mode fiber LC duplex port
- ✓ Fiber distance support: up to 300 m (984 ft.)
- ✓ Wavelength: 850 nm
- ✓ Equivalent to the HPE J9150A / J9150D / JD092A / JD092B transceiver
- ✓ SFP+ standard form factor
- ✓ Supports digital diagnostics monitoring (DDM)
- ✓ Low EMI due to fully metallic housing
- ✓ Supports hot-plugging



Aprašymas

SFP+ Module - HP® / HPE® compatible, affordable premium performance

The Enhanced Small Form Factor Pluggable (SFP+) Transceiver from Intellinet Network Solutions provides a great combination of performance and affordability. Also known as a mini-Gigabit Interface Converter (GBIC), this SFP+ module's metal housing reduces electromagnetic interference and increases its durability.

10G Connectivity

Whether you need a fast connection to your 10-GbE-equipped server or NAS device, or if you simply want to connect two Gigabit switches in your data center at higher speeds to eliminate bottlenecks, the Intellinet Network Solutions 10GBase-SR Fiber SFP+ Optical Transceiver Module is the right choice in getting the speeds and bandwidth you want.

Small Size for High-density Fiber Connections

The transceiver's mini-GBIC form factor helps it take up less space on the equipment it plugs into. It's ideal in environments that require many fiber connections.

Compatible with HP / HPE®

Compatibility in your network is everything, and this SFP+ Transceiver Module delivers. It has been designed, programmed and tested to work with HP / HPE-compatible switches and routers. Since it is set to broadcast the vendor part number J9150A / J9150D / JD092A / JD092B, it is compatible with your HPE gear.

Hot-pluggable

This module is fully hot-pluggable, and that allows you to install the module without rebooting your network switch, so network traffic is uninterrupted.

Digital Diagnostics Monitoring (DDM)

This 10 Gigabit Fiber SFP+ Optical Transceiver Module supports standard digital diagnostics monitoring (DDM) functions, also known as digital optical monitoring (DOM). This lets you monitor parameters of the SFP, such as optical output power, optical input power, temperature, laser bias current, and transceiver supply voltage, in real time.

Techninė specifikacija

Performance	
SFP transceiver type	Fiber optic
Maximum data transfer rate	10000 Mbit/s
Interface type	SFP+
Multi-mode fiber (MMF) supported	Yes
Fiber optic connector	LC
Fiber cable diameters supported (core/cladding)	50/125,62.5/125 µm
SFP transceiver standard	SR
Maximum transfer distance	300 m
Wavelength	850 nm
Tx power (min)	-6 dBmW
Tx power (max)	-1 dBmW

Link budget	4 dB
Networking standards	IEEE 802.3ae, IEEE 802.3z
Copper ethernet cabling technology	10GBASE
Digital Diagnostics Monitoring (DDM)	Yes
Features	
Product colour	Silver
Housing material	Metal
Hot-Plug support	Yes
Brand compatibility	HPE
Power	
Maximum voltage	3.3 V
Power consumption (typical)	1 W
Certificates	
Compliance certificates	CE, RoHS, Federal Communications Commission (FCC)
Operational conditions	
Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	10 - 85%
Weight & dimensions	
Width	14 mm
Depth	57 mm
Height	12 mm
Weight	20 g
Packaging content	
Quantity per pack	1 pc(s)
Packaging data	
Package width	56 mm
Package depth	120 mm
Package height	24 mm
Package weight	50 g
Logistics data	
Master (outer) case width	200 mm
Master (outer) case length	310 mm
Master (outer) case height	250 mm

Master (outer) case gross weight	2.6 kg
Products per master (outer) case	48 pc(s)

Sustainability

Sustainability compliance	Yes
---------------------------	-----

Dokumentai ir vaizdo įrašai

› [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

IC Intracom Vertriebs GmbH

Löhbacher Str. 7, D-58553 Halver, DE

[intellinetnetwork.eu](mailto:info@shopro.lt)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt