

LevelOne 2.5 Gigabit PoE Injector, 60W, 802.3af/at/bt

Gamintojas: **LEVEL ONE** · Modelis: **POI-5005** · EAN: **4015867241608** · Prekės kodas: **960500**



70,91 €

Kaina su PVM

Be PVM: 58,60 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ PoE Standard: IEEE 802.3af/at/bt PoE Compliant.
- ✓ Power Budget: 60W Total Ultra PoE Output.
- ✓ Data Speed: 2.5Gbps Multi-Gigabit (10/100/1000/2500 Mbps).
- ✓ Safety Features: Auto-detection and protection of non-standard devices.
- ✓ Installation: Supports space-saving Wall Mount installation.
- ✓ Transmission: Efficient power delivery over 8 pins.

Aprašymas

The LevelOne POI-5005 is a cutting-edge 60W Ultra PoE injector engineered to solve the power-hungry demands of 2026’s high-bandwidth hardware. Delivering up to 60W of power over all 8 pins, it provides a synchronized energy and data hub for Wi-Fi 7 access points, 4K PTZ cameras, and high-wattage digital signage displays.

Compliant with the latest IEEE 802.3bt standard, this injector utilizes both end-span and mid-span pairs to ensure efficient and stable power delivery. It supports Multi-Gigabit speeds up to 2.5Gbps, making it compatible with the most emerging high-speed network devices while effectively simplifying deployment by removing the need for local power outlets.

Safety is a core priority for the POI-5005, featuring intelligent auto-detection to safeguard your hardware. Its robust design and wall-mount support provide a secure and stable interface, maintaining the operational readiness and performance of your mission-critical professional digital assets.

Techninė specifikacija

Network	
Ethernet interface type	Fast Ethernet, Gigabit Ethernet, 2.5 Gigabit Ethernet
Ethernet LAN data rates	10,100,1000,2500 Mbit/s

Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	PoE+
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bz
Features	
Product colour	Black
Wall mountable	Yes
Easy to install	Yes
Plug and Play	Yes
LED indicators	Power, Data
Power	
AC adapter input voltage	90 - 240 V
Power consumption (typical)	2 W
Total Power over Ethernet (PoE) budget	60 W
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC)
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	0 - 90%
Storage temperature (T-T)	0 - 70 °C
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	145 mm
Depth	64.4 mm
Height	41.8 mm
Weight	200 g
Packaging content	
AC adapter included	Yes
Power cord included	Yes
Logistics data	
Customs product code (TARIC)	851762
Harmonized System (HS) code	851762

Dokumentai ir vaizdo įrašai

› [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

LevelOne

ATSAKINGAS ASMUO ES

Digital Data Communications GmbH

Im Defdahl 10 F, 44141 Dortmund, DE

level1.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt