Lindy 10m RJ45 S/FTP LSZH Network Cable, Grey

Gamintojas: **LINDY** · Modelis: **47268** · EAN: **4002888472685** · Prekės kodas: **960507**

36,91 €

Kaina su PVM

Be PVM: **30,50 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Twisted Pair Patch Cable with RJ45 connectors
- ✓ Connector: Cat.6A / Cable: Cat.7 S/FTP (600Mhz)
- ✓ Integrated snagless connector for latch protection
- ✓ Gold plated pins for better conductivity and elimination of signal loss

Aprašymas

Cat.7 S/FTP LSZH network cable with Cat.6A connectors supports bandwidth up to 600MHz and features a snagless design with gold plated contacts for ethernet standards up to 10 GBase-T.
The Cat.7 cable material for operating frequencies up to 600MHz with taotal braided shielding and foil single-wire shielding (S/FTP) was developed for use in data centres, server rooms, rack mounting of network and control cabinets etc. for networks up to 10GBaseT. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.
The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.
This product uses Cat.7 cable material. The Cat.7 standard originally defined the GG45 connectors, which were intended as a further development of RJ45, but were not able to establish themselves on the market. In the meantime, the RJ45 connector developed to easily meet the requirements of Cat.7, but has never been defined for Cat.7. Therefore the imprint on the cable reads as follows: Cat.6A S/FTP patch cords with 600MHz raw cable .
Available lengths: 0.3m, 0.5m, 1m, 1.5m, 2m, 3m, 5m, 7.5m, 10m, 15m, 20m, 30m.
Available colours: Black, Blue, Grey, Red, White.

Techninė specifikacija

Features	
Cable length	10 m
Cable standard	Cat7
Cable shielding	S/FTP (S-STP)
Connector 1	RJ-45
Connector 2	RJ-45
Product colour	Grey
Connector 1 gender	Male
Connector 2 gender	Male
Connector contacts plating	Nickel/Gold
Connector shielding	Yes
Connector shield material	Aluminium
Jacket material	Low smoke zero halogen (LSZH)
Conductor material	Copper
AWG wire size	26
Frequency	600 MHz
Bend radius (min)	7.8 cm
Operational conditions	
Operating temperature (T-T)	-10 - 60 °C
Storage temperature (T-T)	-20 - 75 °C
Certificates	
Certification	RoHS, REACH, UL, California Proposition 65
Weight & dimensions	
Outer diameter	6.5 mm
Connector 1 dimensions (WxDxH)	11.6 x 22.8 x 8.3 mm
Connector 2 dimensions (WxDxH)	11.6 x 22.8 x 8.3 mm
Packaging data	
Package type	Polybag
Logistics data	
Harmonized System (HS) code	84733080

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Gamintojo ir saugos informacija

GAMINTOJAS

LINDY International Ltd.
Sadler Forster Way Unit 103, TS17 9JY Stockton-on-Tees, GB
lindy.com

ATSAKINGAS ASMUO ES

LINDY-Elektronik GmbH
Markircher Str. 22, 68229 Mannheim, DE
lindy.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt