

LevelOne GEP-1011 tinklo komutatorius Ne-valdomas L2 Gigabit Ethernet (10/100/1000) Maitinimas per Eternetą (PoE) Stalinis / tvirtinamas prie sienos Pilka

Gamintojas: **LEVEL ONE** · Modelis: **GEP-1011** · EAN: **4015867241110** · Prekės kodas: **962562**



167,90 €

Kaina su PVM

Be PVM: **138,76 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Ne-valdomas L2
- ✓ Pagrindinių perjungimo RJ-45 eterneto prievadų skaičius: 9
- ✓ 10BASE-T, 100BASE-TX, 1000BASE-T, 1000BASE-SX, 1000BASE-LX
- ✓ Adreso lentelės dydis: 4000 įrašai Perjungimo pajėgumas: 20 Gbit/s
- ✓ Stalinis / tvirtinamas prie sienos
- ✓ DC Pridėtas maitinimo šaltinis Maitinimas per Eternetą (PoE)



Aprašymas

The LevelOne GEP-1011 is a 10-port Gigabit PoE switch designed for small and medium business networks that need to power and connect IP cameras, wireless access points and VoIP phones over a single Ethernet cable. It provides 8 PoE-capable 10/100/1000Base-T ports, 1 additional

Gigabit RJ45 uplink and 1 Gigabit SFP uplink for flexible connectivity to core switches or fiber backbones.

Compliant with IEEE 802.3af/at, the GEP-1011 delivers a total PoE power budget of 120W, supplying up to 30W per PoE port to compatible devices. Built-in PoE detection and overload protection help ensure safe power delivery, automatically identifying powered devices and cutting power to ports that exceed the budget or are not PoE compliant. This reduces the need for separate power supplies and makes it easier to deploy devices in ceilings, corridors, or remote corners where power outlets are limited.

The combination of one Gigabit copper uplink and one 1000Base-X SFP uplink port gives administrators the freedom to connect using either twisted-pair cabling or fiber, depending on distance and infrastructure. This makes the GEP-1011 suitable as an edge PoE switch in larger networks or as a compact aggregation point for IP surveillance and wireless coverage in branch offices.

With 6KV surge protection and wall-mount support, the GEP-1011 is designed for reliable operation in real-world environments where electrical interference and space constraints are common. Its plug-and-play design requires no software configuration, allowing fast, cost-effective upgrades to a PoE-enabled Gigabit network.

Techninė specifikacija

Management features	
Switch type	Unmanaged
Switch layer	L2
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	9
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
SFP module slots quantity	1
Uplink ports quantity	1
Fiber uplink ports quantity	1
Power connector	DC-in jack
Network	
Networking standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.3af, IEEE 802.3at, IEEE 802.3z
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T, 1000BASE-SX, 1000BASE-LX
Full duplex	Yes
Auto MDI/MDI-X	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
Auto-negotiation	Yes
Data transmission	

MAC address table	4000 entries
Switching capacity	20 Gbit/s
Forwarding rate	14.88 Mpps
Packet buffer memory	0.1875 MB
Design	
Rack mounting	No
Stackable	No
Form factor	Desktop/Wall-Mounting
Product colour	Grey
LED indicators	Link, PoE, ACT, Power
Wall mountable	Yes
Market segment	Business
Performance	
Plug and Play	Yes
Fanless	Yes
Power	
Power source	DC
Power supply included	Yes
DC input voltage	54 V
Input current	2.22 A
Power consumption (typical)	10 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	PoE+
Power over Ethernet plus (PoE+) ports quantity	8
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	120 W
Other features	
Packaging content	Declaration of Conformity
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-45 - 85 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%

Weight & dimensions

Width	217.6 mm
Depth	27.8 mm
Height	108.5 mm
Weight	600 g

Packaging content

Cables included	Power
Quick start guide	Yes

Certificates

Compliance certificates	CE, Federal Communications Commission (FCC), UL
-------------------------	---

Logistics data

Customs product code (TARIC)	846359
Country of origin	China
Harmonized System (HS) code	846359

Dokumentai ir vaizdo įrašai

[> Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

LevelOne

ATSAKINGAS ASMUO ES

Digital Data Communications GmbH
Im Defdahl 10 F, 44141 Dortmund, DE
level1.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt