LogiLink CPV0081 networking cable Black 50 m Cat7 S/FTP (S-STP) Round

Gamintojas: **LOGILINK** · Modelis: **CPV0081** · EAN: **4052792068092** · Prekės kodas: **962773**



56,89 €

Kaina su PVM

Be PVM: **47,02 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Cat.7 Solid network cable for outdoor use
- ✓ Weather resistant, suitable for direct burial
- ✓ 4P 23/1AWG, S/FTP, LSZH, OFC
- ✓ Polyethylene (PE) outer sheath
- ✓ Color-coded PE insulation (1.38 mm)
- ✓ Outer diameter approx. 8.60 mm
- ✓ Conductor diameter 0.57 mm copper
- ✓ Temperature range -20°C ~ +75°C
- ✓ Complies with ISO/IEC 11801, IEC 61156-5, UL444
- ✓ Max. bending radius approx. 70 mm







Aprašymas

Cat.7 outdoor network cable (direct burial cable), LSZH-PE, 50 m" from LogiLink Professional

Designed for outdoor applications, LogiLink Professional Cat.7 direct buried cable meets the most demanding communication requirements, including voice, data, VoIP, video conferencing, security, IP-based cameras and other demanding real-time applications. This high performance Cat.7 cable with PE outer jacket allows installation in dry or wet areas, outdoors or in the ground.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Techninė specifikacija

Features	
Cable length	50 m
Cable standard	Cat7
Cable shielding	S/FTP (S-STP)
Connector 1	No
Connector 2	No
Product colour	Black
Connector 1 gender	No
Connector 2 gender	No
Cable shape	Round
Jacket material	Low smoke zero halogen (LSZH)
Conductor material	Copper
Cable type	Cable on reel
AWG wire size	23/1
Frequency	1000 MHz
Fire-resistant	Yes
Operational conditions	
Operating temperature (T-T)	-20 - 75 °C
Sustainability	
Doesn't contain	Halogen
Certificates	
Compliance certificates	CE
Certification	ISO/IEC 11801, IEC 61156-5, UL444
Weight & dimensions	
Width	300 mm
Depth	300 mm
Height	115 mm
Outer diameter	8.6 mm
Weight	3.3 kg
Packaging content	
Quantity per pack	1 pc(s)
Technical details	
Sustainability compliance	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Gamintojo ir saugos informacija

GAMINTOJAS

2direct GmbH
Langenstück 5, 58579 Schalksmühle, DE
info@2direct.de
2direct.de

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt