

StarTech.com Cisco GLC-LH-SM Compatible SFP Module - 1000BASE-LX/LH - 1GE Gigabit Ethernet SFP - LC 10km - 1310nm - Cisco IE3400, IE3300, IE3200

Gamintojas: **STARTECH** · Modelis: **SFPGLCLHSMST** · EAN: **065030850643** · Prekės kodas: **962881**



57,90 €

Kaina su PVM

Be PVM: **47,85 €**

[Sandėlyje](#)



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 100% CISCO GLC-LH-SM COMPATIBLE: Works with Cisco switches like IE3400, IE3300, IE3200, ME1200, ME2400 and others
- ✓ TECHNICAL SPECS: 1000BASE-LX/LH / 1 Gbps / Single Mode (SMF)/Multi Mode (MMF) / LC Connector / 1310nm / Distances up to 10km (6.2mi)
- ✓ TESTED FOR OEM HOST COMPATIBILITY: Hot-swappable in Cisco routers and switches
- ✓ WORKS WITH MSA COMPLIANT SWITCHES: Also works with switch models from Ubiquiti, D-Link, Netgear, Supermicro, TP-Link and more that accept uncoded modules
- ✓ THE IT PRO'S CHOICE: Designed and built for IT Professionals, this SFP module is backed for life (lifetime of module, not network switch), including free lifetime 24/5 multi-lingual technical assistance.



Aprašymas

1000 Mbps (1 Gbps) | Single & Multi Mode Fiber | LC | 10 km (6.2 mi) | Lifetime Warranty

The SFPGLCLHSMST is a Cisco GLC-LH-SM compatible fiber transceiver module that has been designed, programmed and tested to work with Cisco® brand switches and routers. It delivers dependable 1GbE (1000 Mbps) connectivity over fiber cable, for 1000BASE-LX/LH compliant networks, with a maximum distance of up to 10 km (6.2 mi).

Technical Specifications:

- Wavelength: 1310 nm
- Maximum Data Transfer Rate: 1.25 Gbps
- Type: Single Mode / Multimode Fiber
- Connection Type: LC Connector
- Maximum Transfer Distance: 10 km (6.2 mi) - SM / 1 km (0.6 mi) - MM
- MTBF: 3,092,408 hours
- Power Consumption: Less than 1 Watt
- Digital Diagnostics Monitoring (DDM): No

This SFP fiber module is hot-swappable, making upgrades and replacements seamless by minimizing network disruptions.

StarTech.com SFPs

All StarTech.com SFP & SFP+ transceiver modules are backed by a lifetime warranty and free lifetime multilingual technical support. StarTech.com offers a wide variety of SFP modules and direct-attach SFP cables, providing the convenience and reliability you need to ensure dependable network performance.

Techninė specifikacija

Performance	
SFP transceiver type	Fiber optic
Maximum data transfer rate	1250 Mbit/s
Interface type	SFP
Multi-mode fiber (MMF) supported	Yes
Fiber optic connector	LC
SFP transceiver standard	LH, LX
Maximum transfer distance	10000 m
Wavelength	1310 nm
Networking standards	IEEE 802.3z
Duplex system	Full, Half
Digital Diagnostics Monitoring (DDM)	No
Wavelength-division multiplexing (WDM)	No
Features	
Product colour	Stainless steel
Hot-swap	Yes
Mean time between failures (MTBF)	3092408 h
Power	
Power consumption (typical)	1 W

Certificates

Compliance certificates	RoHS
Certification	CE, FCC, UL

Operational conditions

Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	30 - 70%

Weight & dimensions

Width	12 mm
Depth	60 mm
Height	10 mm
Weight	20 g

Packaging content

Quantity per pack	1 pc(s)
-------------------	---------

Packaging data

Package width	93 mm
Package depth	114 mm
Package height	34 mm
Package weight	46 g

Logistics data

Master (outer) case width	342 mm
Master (outer) case length	426 mm
Harmonized System (HS) code	85369010
Master (outer) case height	354 mm
Products per master (outer) case	108 pc(s)

Dokumentai ir vaizdo įrašai[› Gaminio lankstinukas](#)**Gamintojo ir saugos informacija**

GAMINTOJAS

StarTech.com Ltd.Artisans Crescent 45, N5V 5E9 Ontario, London,
CAstartech.com

ATSAKINGAS ASMUO ES

StarTech.com LimitedLaarderhoogtweg 25, 1101 EB Amsterdam, NL
startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURUV. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt