

StarTech.com 5m Red Slim CAT6 Ethernet Cable, Snagless, 100W PoE, UTP, LSZH, 28AWG Pure Bare Copper Wire, Slim RJ45 Network Patch Cord w/Strain Reliefs, Individually Tested

Gamintojas: **STARTECH** · Modelis: **N6PAT5MRDS** · EAN: **065030918879** · Prekės kodas: **963071**



15,90 €

Kaina su PVM

Be PVM: **13,14 €**

[Sandėlyje](#)




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ **Streamline Cabling in Tight Spaces**: Slim Cat6 Cables are 36% thinner than standard CAT6 network cables, offering greater flexibility and easier routing in dense IT setups
- ✓ **Built for Performance**: Supports 10Gbps speeds and 100W PoE++ (IEEE 802.3bt Type 4) with 28AWG pure bare copper wire and 50-micron gold-plated contacts for reliable signal integrity; Flexible Low-Smoke Zero Halogen (LSZH) jacket withstands tight bends
- ✓ **Tested for Reliable Uptime**: Compliant with ANSI/TIA-568-C.2 standards for guaranteed Cat6 performance up to 250MHz; Individually Tested for minimal Near-End Crosstalk (NEXT) and Return Loss (RL)
- ✓ **Enhance Access and Airflow**: Slim Cat6 cables improve access for troubleshooting and airflow between devices; Connect reliably to PoE devices such as IP or boardroom cameras; LSZH jacket is safe for confined spaces and emits low-toxicity fumes if combusted
- ✓ **The IT Pro's Choice**: Designed for reliability in edge and on-prem deployments, our network cables are lab-tested and field-proven for seamless integration and maximum uptime; Backed by free lifetime 24/5 multi-lingual technical assistance





Aprašymas

Route Slim Cat6 cables through high density installations for optimal flexibility and airflow

This slim CAT6 cable meets all Category 6 patch cable specifications to deliver a reliable Gigabit and Power over Ethernet (PoE) network connection in high-density network installations.

Improved Airflow

The Slim Cat6 Patch Cord is 36% thinner than standard Cat6 Ethernet cables, enabling greater airflow and heat dissipation in confined spaces. The Slim Cat6 Ethernet cable is also more flexible, for easier cable routing in crowded network racks and patch panels.

This cable features snagless connectors that protect the RJ45 clips during installation, reducing snags or breakage when routing through narrow gaps or in between devices.

Durable Construction

The Slim Cat6 Cable features 50-micron gold RJ45 contacts that ensure a precise fit to minimize wear and signal loss. The 4-pair Unshielded Twisted Pair (UTP) construction utilizes 28AWG Pure Bare Copper Wire for improved conductivity and low resistance. The flexible Low Smoke Zero Halogen (LSZH) flame-retardant jacket emits low smoke and toxic fumes when exposed to extreme heat or in the event of a fire. This enables safer installations in poorly-ventilated areas including some industrial settings, self-contained environments such as trains and aircraft, as well as residential settings where compliance with building codes must be considered.

Tested for Reliability

Each cable is individually tested using a Fluke® DSX2-8000 CableAnalyzer™ to meet ANSI/TIA-568.2-D Category 6 specifications, ensuring consistent signal integrity with minimal Near-End Crosstalk (NEXT) and Return Loss (RL). Reliably deliver up to 100W of PoE++ to power a remote networking devices, including PoE switches and boardroom cameras. This Slim Cat6 Patch Cable complies with IEEE 802.3bt Type 4 PoE++ specifications.

Techninė specifikacija

Features	
Cable length	5 m
Cable standard	Cat6
Cable shielding	U/UTP (UTP)

Connector 1	RJ-45
Connector 2	RJ-45
Product colour	Red
Connector 1 gender	Male
Connector 2 gender	Male
Cable shape	Round
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Gold
Jacket material	Low smoke zero halogen (LSZH)
Conductor type	Stranded
Conductor material	Copper
Cabling technology	10/100/1000Base-T(X)
Ethernet interface type	Fast Ethernet, Gigabit Ethernet
Networking standards	IEEE 802.3bt
AWG wire size	28
Data transfer rate	1000 Mbit/s
Frequency	250 MHz
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	PoE++ (4PPoE)
Total Power over Ethernet (PoE) budget	100 W
Snagless cable boot	Yes
Plug and Play	Yes
Operational conditions	
Operating temperature (T-T)	10 - 60 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 80%
Certificates	
Compliance certificates	CE, RoHS
Weight & dimensions	
Outer diameter	3.6 mm
Packaging content	
Quantity per pack	1 pc(s)
Packaging data	

Package width	200 mm
Package depth	220 mm
Package height	15 mm
Package weight	94 g
Logistics data	
Master (outer) case width	420 mm
Master (outer) case length	420 mm
Master (outer) case height	250 mm
Products per master (outer) case	160 pc(s)

Dokumentai ir vaizdo įrašai

> [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS	ATSAKINGAS ASMUO ES	PLATINTOJAS
StarTech.com Ltd.	StarTech.com Limited	MB KOMPIUTERIŲ GURU
Artisans Crescent 45, N5V 5E9 Ontario, London, CA	Laarderhoogtweg 25, 1101 EB Amsterdam, NL	V. Nagevičiaus g. 3, LT-08237 Vilnius
startech.com	startech.com	info@shopro.lt