

TP-Link ISM311LS network transceiver module Fiber optic 1250 Mbit/s SFP 1310 nm

Gamintojas: **TP-LINK** · Modelis: **ISM311LS** · EAN: **1210002601955** · Prekės kodas: **963977**



39,91 €

Kaina su PVM

Be PVM: **32,98 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Single-mode SFP LC Transceiver
- ✓ Supports Digital Diagnostic Monitoring (DDM)
- ✓ Compatible with Small Form Pluggable Multi-Source Agreement (SFP-MSA)
- ✓ Hot-Pluggable with maximum flexibility
- ✓ Industrial Product Operating Temperature Range: -40-85°C

Aprašymas

ISM311LS is an industrial SFP Module introduced for extending transfer distance. Attached to our industrial switches, ISM311LS can extend the distance to 20km. Users can choose whether and which items to use the fiber modules according to the demand in order to lower cost.

Techninė specifikacija

Performance	
SFP transceiver type	Fiber optic
Maximum data transfer rate	1250 Mbit/s
Interface type	SFP
Single-mode fiber (SMF) supported	Yes
Fiber optic connector	LC
Fiber cable diameters supported (core/cladding)	9/125 μm

Maximum transfer distance	20000 m
Wavelength	1310 nm
Ethernet interface type	1.25 Gigabit Ethernet
Networking standards	IEEE 802.3z
Features	
Product colour	Grey
Hot-swap	Yes
Power	
Input voltage	3.3 V
Certificates	
Certification	FCC, CE
Operational conditions	
Minimum operating temperature	-40 °C
Maximum operating temperature	85 °C
Storage temperature (T-T)	-40 - 85 °C
Operating relative humidity (H-H)	5 - 85%
Storage relative humidity (H-H)	5 - 85%
Weight & dimensions	
Width	56.4 mm
Depth	13.4 mm
Height	11 mm
Packaging content	
Quantity per pack	1 pc(s)

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH

Niederkasseler Lohweg 175, 40547 Düsseldorf,
DE

[tp-link.com](https://www.tp-link.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt