Intellinet Gigabit Ethernet to SFP Media Converter, 10/100/1000Base-Tx to SFP slot, empty

Gamintojas: **INTELLINET** · Modelis: **510493** · EAN: **766623510493** · Prekės kodas: **964079**



123,90 €

Kaina su PVM

Be PVM: **102,40 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Data transfer rate: 1000 Mbps
- ✓ 10/100/1000Base-TX auto-sensing RJ45 port, maximum distance 100 m / 300 ft. (Cat5e and better)
- ✓ RJ45 port with Auto MDI/MDI-X support
- ✓ SFP (Small Form Factor Pluggable) optical transceiver module port (SFP module not included)
- ✓ Module port for Gigabit multimode or single-mode Mini GBIC 1.25G SFP-type fibre modules
- ✓ Status LEDs for power and Link/TX for both ports
- ✓ External power adapter, 5 VDC
- ✓ Functions as a stand-alone converter or can be used with the 14-slot media converter chassis, model 507356
- ✓ Three-Year Warranty













Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Aprašymas

The Intellinet Network Solutions Gigabit Ethernet to SFP Media Converter is completely transparent to the network so the network performs exactly the way it did before - only now it can support both copper and fibre mediums.

Expands the Size of an Existing Network

Provides fibre connectivity to Ethernet segments, allowing for even further networking expansion between extended workgroups. Also provides building-to-building connectivity without the need for the cost and disruption associated with the installation of additional routers.

Enhances the Distance between Networking Devices

Connecting the converter to fibre segments can further extend distances between networking nodes. This can be achieved by direct connection between the converter and a fibre-based node or networking device.

Cabling Flexibility

Network managers can install fibre cabling anywhere within a network without changing the arrangement of copper-based Ethernet. The compact size of the converter allows it to be easily deployed in any narrow desktop location or to be used in a wall-mount installation. Several converters can be simultaneously installed into a 19"; rack-mountable chassis.

Techninė specifikacija

Network	
Maximum data transfer rate	1000 Mbit/s
Converter input interface	10Base-T, 100Base-TX, 1000Base-TX
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3z
Ethernet interface type	Fast Ethernet, Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Data transfer rate	1000 Mbit/s
Auto MDI/MDI-X	Yes
Duplex system	Full
Cable types supported	Cat5e, Fiber
Performance	
Maximum transfer distance	100 m
Features	
Internal	No
LED indicators	Link, Power
Product colour	Black
Housing material	Metal
Ports & interfaces	
Fiber optic connector	SFP

Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
Power	
Input voltage	12 V
Input current	1.2 A
Power consumption (max)	5 W
External power adapter	Yes
Weight & dimensions	
Width	70 mm
Depth	96 mm
Height	26 mm
Weight	170 g
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	10 - 80%
Packaging content	
User guide	Yes
Certificates	
Certification	FCC Class A, CE
Logistics data	
Harmonized System (HS) code	85176990

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

IC Intracom Vertriebs GmbH
Löhbacher Str. 7, D-58553 Halver, DE
intellinetnetwork.eu

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt