ACT Powercord C14 IEC Lock+ Dual Locking - C15 IEC Lock+ black 3 m, PC3876

Gamintojas: **ACT** · Modelis: **PL0043** · EAN: **8716065565881** · Prekės kodas: **964387**

33,90 €

Kaina su PVM

Be PVM: **28,02 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Cable length: 3 m
- ✓ Connectors: C14 Dual locking IEC Lock+ - C15 IEC Lock+
- ✓ Protects against accidental disconnection in critical equipment, PDUs, servers, network equipment, etc
- ✓ The C15 connector is high temperature resistant up to 120°C
- ✓ Suitable for all PDUs; PDU doesn't need a locking mechanism of its own
- ✓ PDU side locks at the top and side
- ✓ Minimizes risks of damage and downtime
- ✓ Maximum load: 10A/250V~
- ✓ Color: black

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Aprašymas

The ACT IEC Lock power cable offers locking at both ends: C15 IEC Lock+ connector on one side and the C14 IEC Lock+ Dual Locking connector on the PDU side. The C14 connector locks at the top and side, providing additional protection against accidental disconnection from the PDU. The C15 connector is high temperature resistant up to 120°.

The locking mechanism is universal and works with all major PDU brands. The PDU doesn’t need to have its own locking mechanism and no tools are required.

The IEC Lock prevents accidental disconnection/release of the cable from both the equipment and the PDU. This minimizes the risk of damage and downtime. The power cables are available in a range of colors for easy identification.

Techninė specifikacija

Features	
Product colour	Black
Connector 1 gender	Male
Connector 2 gender	Female
Cable length	3 m
Connector 1	IEC C14
Connector 2	IEC C15
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Jacket material	Neoprene
Number of conductors	3
Conductor cross section	1 mm²
Power	
Input voltage	250 V
Input current	10 A
Operational conditions	
Operating temperature (T-T)	-5 - 40 °C
Packaging data	
Quantity per pack	1 pc(s)

Gamintojo ir saugos informacija

GAMINTOJAS

Intronics BV
Koolhovenstraat 1E, 3772 MT Barneveld, NL
intronics.nl

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt