

ACT Black 5 meters U/UTP CAT6A LSZH Slimline patch cable with RJ45 connectors 90° angled down to 90° angled down

Gamintojas: **ACT** · Modelis: **DD5905** · EAN: **8716065571158** · Prekės kodas: **964501**



16,90 €

Kaina su PVM

Be PVM: **13,97 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Cable length: 5 meters
- ✓ Connectors: RJ45 90° angled down - RJ45 90° angled down
- ✓ Ideal for situations where space is limited without stressing the bend radius
- ✓ Full copper 28AWG wires, 50μ gold-plated RJ45 contacts
- ✓ Outer diameter jacket of only 3.6mm to improve airflow in cabinets
- ✓ Low Smoke Zero Halogen (LSZH) cable jacket reduces the risk of high concentrations of toxic gases in case of cable damage due to fire or short circuit
- ✓ Conforms to international standard ANSI/TIA-568.2-D
- ✓ Cables are 100% tested
- ✓ Colour: Black



Aprašymas

CAT6A U/UTP slimline datacenter patch cables are smaller in diameter (3.6mm vs 5.9mm) than regular CAT6A patch cords. The bend radius is smaller compared to standard patch cords. This results in better airflow in the server rack or network cabinet.

The patch cable has two 90° angled down RJ45 connectors. Ideal for situations where space is limited without compromising the bend radius. For example in network cabinets and behind equipment.

Also available with a straight, 90° angled up, left or right RJ45 connector.

The use of a LSZH (Low Smoke Zero Halogen) cable jacket reduces the risk of high concentrations of toxic gases if the cable is damaged by fire or short circuit.

The ACT U/UTP patch cable has full copper 28AWG wires and 50μ gold-plated RJ45 contacts and complies with the international standard ANSI/TIA-568.2-D.

Techninė specifikacija

Features	
Cable length	5 m
Cable standard	Cat6a
Cable shielding	U/UTP (UTP)
Connector 1	RJ-45
Connector 2	RJ-45
Product colour	Black
Connector 1 gender	Male
Connector 2 gender	Male
Connector 1 form factor	Down
Connector 2 form factor	Down
Connector contacts plating	Gold
Jacket material	Low smoke zero halogen (LSZH)
Cable shape	Round
Conductor material	Copper
Networking standards	IEEE 802.3at
AWG wire size	28
Frequency	500 MHz
Bend radius (min)	1.5 cm
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	PoE+
Total Power over Ethernet (PoE) budget	30 W

Operational conditions

Operating temperature (T-T)	-20 - 60 °C
-----------------------------	-------------

Sustainability

Doesn't contain	Halogen
-----------------	---------

Certificates

Compliance certificates	CE
-------------------------	----

Weight & dimensions

Outer diameter	3.6 mm
----------------	--------

Packaging content

Quantity per pack	1 pc(s)
-------------------	---------

Gamintojo ir saugos informacija

GAMINTOJAS

Intronics BV

Koolhovenstraat 1E, 3772 MT Barneveld, NL

intronics.nl

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt