ACT Black 15.0 meter U/UTP, CAT6 patch cable with RJ45 connectors

Gamintojas: **ACT** · Modelis: **AC4015** · EAN: **8716065488135** · Prekės kodas: **964883**



22,91 €

Kaina su PVM

Be PVM: **18,93 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Cable length: 15 meters
- ✓ Full copper 24AWG wires, 50µ gold RJ-45 contacts
- ✓ For 10/100/1000 Mbps Networks
- ✓ Specifications comply to international standards
- ✓ Cables are 100% tested








Aprašymas

The ACT U/UTP patch cable meets the CAT6 specifications and can be used in 10/100/1000Mbps networks.

ACT patch cables are fitted with full copper conductors and comply with the ANSI/TIA-568.2-D performance requirements. The combination of a well-structured copper data network, reliable active devices and copper patch cables ensure a trouble-free operating network which will be stable for a

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

long period of time.

By applying materials that comply with international standards, your active network devices will be able to perform optimally, without failures. For PoE (Power over Ethernet) applications, it is important to use patch cables with full copper conductors. All ACT patch cables have full copper conductors.

Techninė specifikacija

Features	
Cable length	15 m
Cable standard	Cat6
Cable shielding	U/UTP (UTP)
Connector 1	RJ-45
Connector 2	RJ-45
Product colour	Black
Connector 1 gender	Male
Connector 2 gender	Male
Connector contacts plating	Gold
Jacket material	Polyvinyl chloride (PVC)
Cable shape	Round
Conductor material	Copper
Cabling technology	10/100/1000Base-T(X)
Ethernet interface type	Gigabit Ethernet
AWG wire size	24
Data transfer rate	1000 Mbit/s
Frequency	250 MHz
Operational conditions	
Operating temperature (T-T)	-20 - 60 °C
Certificates	
Compliance certificates	CE
Packaging content	
Quantity per pack	1 pc(s)
Packaging data	
Package width	200 mm
Package depth	50 mm
Package height	250 mm
Package weight	555 g

Package type	Polybag
Logistics data	
Harmonized System (HS) code	84733080
Technical details	
Sustainability compliance	Yes

Gamintojo ir saugos informacija

GAMINTOJAS

Intronics BV
Koolhovenstraat 1E, 3772 MT Barneveld, NL
intronics.nl

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.