ACT USB4 80Gbps Thunderbolt 5 cable 240W USB Type-C, USB-IF certified, 1.5 meters

Gamintojas: **ACT** · Modelis: **AC7452** · EAN: **8716065587654** · Prekės kodas: **964887**



27,90 €

Kaina su PVM

Be PVM: **23,06 €**

Sandėlyje


Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Official USB-IF certified USB4® 80Gbps cable for connecting and charging USB-C devices
- ✓ Thunderbolt™ 5 support
- ✓ Data transfer speed up to 80Gbps; Asymmetric data: 120Gbps + 40Gbps
- ✓ Power Delivery: Extended Power Range (EPR) up to 48V @ 5A = 240W
- ✓ DisplayPort Alternate Mode 2.1 support with a maximum video resolution up to 16K @ 120Hz
- ✓ Connectors: USB Type-C male – USB Type-C male
- ✓ Cable length: 1.5 meters
- ✓ Backwards compatible with Thunderbolt™ 3/4, USB 3.2, USB 3.1, USB 3.0 and USB 2.0













Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Aprašymas

The AC7452 is an official USB-IF certified USB Type-C® cable that supports USB4® 80Gbps and Thunderbolt™5. The AC7452 can reach a maximum data transfer speed up to 80Gbps and can handle 240W power because of the Extended Power Range. The AC7452 supports a maximum resolution of one 16K monitor or two 8K monitors in daisy chain mode. Backwards compatible with Thunderbolt™4, Thunderbolt™3, USB 3.2, USB 3.1, USB 3.0, and USB 2.0.

Fast data, high power and video via ONE USB4® cable

The AC7452 includes an intelligent e-marker chip. This chip communicates with the connected devices, e.g. laptop or charger, which features are supported by the cable. The AC7452 can handle data, power and video.

USB4® version 2.0 80Gbps and Thunderbolt™5 support

The AC7452 USB-C cable includes the USB4® technology with Thunderbolt™5. The cable supports a maximum data transfer speed up to 80Gbps. The cable also supports asymmetric data transfer: 120Gbps + 40Gbps. Which results in a higher download speed and lower upload speed. This is useful in situations where high demand in download is needed.

Power Delivery: Extended Power Range 240W

The EPR adds additional Power Delivery profiles, 28V, 36V and 48V, to the USB4® cable. The AC7452 includes the 48V profile that enables the cable to transfer a maximum power of 240W. As cables with SPR (Standard Power Range) only can deliver 60W.

DisplayPort Alternate Mode protocol

The USB4® version 2.0 cable supports the DisplayPort Alternate Mode (DP Alt Mode) 2.1 protocol to distribute video over USB-C. The AC7452 has a maximum resolution of one 16K @ 120Hz monitor or two 8K @ 120Hz monitors in MST setup.

Official USB-IF certified

The AC7452 is officially certified by the USB-IF corporation. The cable is tested to the highest standards by USB-IF. The official USB-IF logo can be found on the connector. ACT is member of the USB Implementers Forum, Inc.

Techninė specifikacija

Features	
USB version	USB4 Gen 4x2
Connector 1	USB C
Connector 2	USB C
Connector 1 gender	Male
Connector 2 gender	Male
Product colour	Black
Connector 1 form factor	Straight
Connector 2 form factor	Straight
AWG wire size	34/24
Cable jacket material	Thermoplastic elastomer (TPE)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Conductor material	Tinned copper
Maximum data transfer rate	80 Gbit/s
Cable type	Round cable
Fast charging	Yes
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	240 W
USB Type-C DisplayPort Alternate Mode	Yes
DisplayPort version	2.1
Maximum resolution	15360 x 8640 pixels
Maximum refresh rate	120 Hz
Thunderbolt technology	Yes
Thunderbolt version	5
Power	
Input voltage	48 V
Input current (max)	5 A
Weight & dimensions	
Cable length	1.5 m
Cable diameter	5.5 mm
Packaging content	
Quantity per pack	1 pc(s)

Dokumentai ir vaizdo įrašai

- Gaminio lankstinukas
- Atitikties deklaracija

Gamintojo ir saugos informacija

GAMINTOJAS

Intronics BV
Koolhovenstraat 1E, 3772 MT Barneveld, NL
intronics.nl

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

- Atitikties deklaracija