

ACT AK3875 HDMI cable 5 m HDMI Type A (Standard) Black

Gamintojas: **ACT** · Modelis: **AK3875** · EAN: **8716065563436** · Prekės kodas: **964912**



29,90 €

Kaina su PVM

Be PVM: **24,71 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ HDMI Premium High Speed v2.0 LSZH cable
- ✓ Max. resolution: 3840x2160 (4K) @ 60Hz
- ✓ Low Smoke Zero Halogen (LSZH) cable jacket reduces the risk of high concentrations of toxic gases in case of cable damage due to fire or short circuit
- ✓ Suitable for sensitive applications due to low RFI / EMI
- ✓ HDMI version: v2.0
- ✓ Bandwidth: 18Gbps
- ✓ Full copper cable with gold-plated contacts



Aprašymas

The ACT HDMI LSZH Premium High Speed v2.0 cables ensure crystal clear audio and video throughput with a maximum resolution of 4K@60Hz. With full copper conductors and gold-plated connectors, the cable guarantees a reliable and high-quality transmission. The Low Smoke Zero Halogen (LSZH) cable jacket reduces the risk of high concentrations of toxic gases in case of cable damage due to fire or short circuit. Additionally, the cable's thin plate shielding reduces RFI/EMI, making it ideal for sensitive applications.

Resolution of 4K @ 60Hz

The HDMI cable supports a resolution of 3840x2160 @ 60Hz. Furthermore, the cable supports High Dynamic Range (HDR) video for expansive contrast ratio and color accuracy, HDCP 2.2, EDID, Multi-channel audio, Dolby True HD, and DTS-HD Master Audio.

Thin plate shielding for low EMI/RFI

An additional thin plate is used to provide extra shielding to reduce Electromagnetic Interference (EMI) and Radio Frequency Interference (RFI).

LSZH cable jacket

The cable has a LSZH (Low Smoke Zero Halogen) cable jacket that reduces the risk of high concentrations of toxic gases in case the cable is damaged due to fire or short circuit.

User scenarios

Medical applications: High-resolution imaging is critical in radiology for detailed diagnosis. The HDMI LSZH cable is used to connect imaging equipment to large displays. The low RFI/EMI minimizes interference with sensitive medical devices.

Nautical applications: The vessel's bridge uses high-definition displays for navigation, radar, and other systems.

Data center applications: Data centers require high-resolution displays for monitoring system performance and security. The LSZH jacket ensures safety by reducing toxic gas emissions in case of a fire.

Educational applications in lecture halls and auditoriums: Provides clear and detailed visuals for large audiences.

Corporate applications in meeting rooms and conference centers: Executive meeting rooms and conference centers require high-definition displays for video conferencing, presentations, and collaborative work.

Techninė specifikacija

Features	
Cable length	5 m
Connector 1	HDMI Type A (Standard)
Connector 2	HDMI Type A (Standard)
Connector 1 gender	Male
Connector 2 gender	Male
HDMI cable type	Premium High Speed HDMI cable
Product colour	Black
Connector contacts plating	Gold
Connector 1 form factor	Straight
Connector 2 form factor	Straight

HDMI version	2
Supported graphics resolutions	3840 x 2160
Dolby technologies	DTS-HD Master Audio, Dolby TrueHD
Audio Return Channel (ARC)	Yes
HDMI Ethernet channel	Yes
HDCP	Yes
HDCP version	2.2
Data transfer rate	18 Gbit/s
High Dynamic Range (HDR) supported	Yes
Maximum refresh rate	60 Hz
AWG wire size	30
Connector housing material	Plastic
Cable material	Tinned copper
Cable type	Round cable
Cable jacket material	Low smoke zero halogen (LSZH)
Magnetically shielded	Yes
Shield material	Aluminium
Bending radius (min)	7.2 cm
Plug and Play	Yes
Colour sampling	4:4:4
Weight & dimensions	
Cable diameter	6 mm
Packaging data	
Quantity per pack	1 pc(s)
Matmenys ir svoris	
Svoris	1,00kg

Dokumentai ir vaizdo įrašai

› [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Intronics BV

Koolhovenstraat 1E, 3772 MT Barneveld, NL

intronics.nl

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt