


# ACT Green 5 meter LSZH U/FTP CAT6A datacenter slimline patch cable snagless with RJ45 connectors

Gamintojas: **ACT** · Modelis: **DC7705** · EAN: **8716065442212** · Prekės kodas: **964988**



## 17,90 €

Kaina su PVM

Be PVM: **14,79 €**

**Sandėlyje**





**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ Full copper 32AWG wires, 50μ gold RJ-45 contacts
- ✓ Outer diameter jacket of only 3.8mm to improve air flow in cabinet
- ✓ Snagless boots
- ✓ For channel applications
- ✓ Specifications comply to international standards
- ✓ Cables are 100% tested
- ✓ 5 Year warranty



## Aprašymas

CAT6A U/FTP slimline datacenter ethernet cables are smaller in diameter (3.8mm vs 5.9mm) than regular CAT 6A patch cords. The bending radius is lower in comparison with regular patch cords. This results in a better airflow in the cabinet.

Although, ISO/IEC and TIA standards describe the use of patch cords between 22 and 26 AWG, it is possible to use 32 AWG patch cables. This results

in a higher attenuation, particularly at higher frequencies. ACT therefore recommends a shorter permanent link length than with regular 24 AWG patch cords. So this higher attenuation can be accommodated.

ACT advises a maximum bundle size of 24 cables in PoE applications. In this case the temperature of the cables, that are delivering PoE deployments, will not increase. The standard, ANSI TSB-184-A, limits the maximum temperature increasement, to less than 15 degrees Celsius above the ambient temperature, for the center cable in a bundle.

## Techninė specifikacija

| Features                    |                               |
|-----------------------------|-------------------------------|
| Cable length                | 5 m                           |
| Cable standard              | Cat6a                         |
| Cable shielding             | U/FTP (STP)                   |
| Connector 1                 | RJ-45                         |
| Connector 2                 | RJ-45                         |
| Product colour              | Green                         |
| Connector 1 gender          | Male                          |
| Connector 2 gender          | Male                          |
| Connector contacts plating  | Gold                          |
| Jacket material             | Low smoke zero halogen (LSZH) |
| Conductor material          | Copper                        |
| AWG wire size               | 32                            |
| Frequency                   | 500 MHz                       |
| Operational conditions      |                               |
| Operating temperature (T-T) | -20 - 75 °C                   |
| Weight & dimensions         |                               |
| Outer diameter              | 3.8 mm                        |
| Packaging content           |                               |
| Quantity per pack           | 1 pc(s)                       |
| Logistics data              |                               |
| Harmonized System (HS) code | 84733080                      |

## Gamintojo ir saugos informacija

### GAMINTOJAS

#### Intronics BV

Koolhovenstraat 1E, 3772 MT Barneveld, NL

[intronics.nl](https://www.intronics.nl)

### PLATINTOJAS

#### MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

[info@shopro.lt](mailto:info@shopro.lt)