ACT Yellow 7 meter LSZH U/FTP CAT6A datacenter slimline patch cable snagless with RJ45 connectors

Gamintojas: **ACT** · Modelis: **DC7807** · EAN: **8716065510188** · Prekės kodas: **964992**

20,90 €

Kaina su PVM

Be PVM: **17,27 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Snagless boots
- ✓ For connecting active equipment
- ✓ Specifications comply to international standards
- ✓ Cables are 100% tested

Aprašymas

CAT6A U/FTP slimline datacenter ethernet cables are smaller in diameter (3.8mm vs 5.9mm) than regular CAT 6A patch cords. The bending radius is lower in comparison with regular patch cords. This results in a better airflow in the server rack/network cabinet.

Although, ISO/IEC and TIA standards describe the use of patch cords between 22 and 26 AWG, it is possible to use 32 AWG patch cables. This results in a higher attenuation, particularly at higher frequencies.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

ACT advises a maximum bundle size of 24 cables in PoE applications. In this case the temperature of the cables, that are delivering PoE deployments, will not increase. The standard, ANSI TSB-184-A, limits the maximum temperature increasement, to less than 15 degrees Celsius above the ambient temperature, for the center cable in a bundle.

Techninė specifikacija

Features	
Cable length	7 m
Cable standard	Cat6a
Cable shielding	U/FTP (STP)
Connector 1	RJ-45
Connector 2	RJ-45
Product colour	Yellow
Connector 1 gender	Male
Connector 2 gender	Male
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Gold
Jacket material	Low smoke zero halogen (LSZH)
Conductor material	Copper
AWG wire size	32
Frequency	500 MHz
Operational conditions	
Operating temperature (T-T)	-20 - 75 °C
Logistics data	
Warranty period	5 year(s)

Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

Intronics BV
Koolhovenstraat 1E, 3772 MT Barneveld, NL
intronics.nl

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.