

ACT Black 5 m U/FTP CAT6A LSZH Slimline patch cable with RJ45 connectors 90° angled right to straight

 Gamintojas: **ACT** · Modelis: **DA2905** · EAN: **8716065571073** · Prekės kodas: **965023**


19,90 €

Kaina su PVM

 Be PVM: **16,45 €**

Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Connectors: RJ45 90° angled right - RJ45 straight
- ✓ Ideal for situations where space is limited without stressing the bend radius
- ✓ Full copper 32AWG wires, 50μ gold-plated RJ45 contacts
- ✓ Outer diameter jacket of only 3.8mm to improve airflow in cabinets
- ✓ Low Smoke Zero Halogen (LSZH) cable jacket reduces the risk of high concentrations of toxic gases in case of cable damage due to fire or short circuit
- ✓ Conforms to international standards
- ✓ Cables are 100% tested



Space saving slimline cables



Advantages Slimline cable



Aprašymas

CAT6A U/FTP slimline datacenter patch cables are smaller in diameter (3.8mm vs 5.9mm) than regular CAT6A patch cords. The bend radius is smaller compared to standard patch cords. This results in better airflow in the server rack or network cabinet.

The patch cable has a straight RJ45 connector and a 90° angled right RJ45 connector. Ideal for situations where space is limited without compromising the bend radius. For example in network cabinets and behind equipment.

Also available with a 90° angled up, down or left RJ45 connector.

The use of a LSZH (Low Smoke Zero Halogen) cable jacket reduces the risk of high concentrations of toxic gases if the cable is damaged by fire or short circuit.

The ACT U/FTP patch cable has full copper 32AWG wires and 50μ gold-plated RJ45 contacts and complies with international standards.

Techninė specifikacija

Features	
Cable length	5 m
Cable standard	Cat6a
Cable shielding	U/FTP (STP)
Connector 1	RJ-45
Connector 2	RJ-45
Product colour	Black
Connector 1 gender	Male
Connector 2 gender	Male
Connector 1 form factor	Angled
Connector 2 form factor	Straight
Connector contacts plating	Gold
Jacket material	Low smoke zero halogen (LSZH)
Conductor material	Copper
AWG wire size	32
Frequency	500 MHz
Operational conditions	
Operating temperature (T-T)	-20 - 60 °C
Certificates	
Certification	CE
Weight & dimensions	
Outer diameter	3.8 mm

Gamintojo ir saugos informacija

GAMINTOJAS

Intronics BV

Koolhovenstraat 1E, 3772 MT Barneveld, NL

intronics.nl

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt