

ACT White 10 meter LSZH U/FTP CAT6A datacenter slimline patch cable snagless with RJ45 connectors

Gamintojas: **ACT** · Modelis: **DC6910** · EAN: **8716065509717** · Prekės kodas: **965132**



27,90 €

Kaina su PVM

Be PVM: **23,06 €**

Sandėlyje



Prekė internetu

Nuskuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Cable length: 10 m
- ✓ Full copper 32AWG wires, 50μ gold RJ-45 contacts
- ✓ Outer diameter jacket of only 3.8mm to improve air flow in cabinet
- ✓ Snagless boots
- ✓ For connecting active equipment
- ✓ Specifications comply to international standards
- ✓ Cables are 100% tested



Aprašymas

CAT6A U/FTP slimline datacenter ethernet cables are smaller in diameter (3.8mm vs 5.9mm) than regular CAT 6A patch cords. The bending radius is lower in comparison with regular patch cords. This results in a better airflow in the server rack/network cabinet.

Although, ISO/IEC and TIA standards describe the use of patch cords between 22 and 26 AWG, it is possible to use 32 AWG patch cables. This results in a higher attenuation, particularly at higher frequencies.

ACT advises a maximum bundle size of 24 cables in PoE applications. In this case the temperature of the cables, that are delivering PoE deployments, will not increase. The standard, ANSI TSB-184-A, limits the maximum temperature increasement, to less than 15 degrees Celsius above the ambient temperature, for the center cable in a bundle.

Techninė specifikacija

Features	
Cable length	10 m
Cable standard	Cat6a
Cable shielding	U/FTP (STP)
Connector 1	RJ-45
Connector 2	RJ-45
Product colour	White
Connector 1 gender	Male
Connector 2 gender	Male
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Gold
Jacket material	Low smoke zero halogen (LSZH)
Cable shape	Round
Conductor material	Copper
AWG wire size	32
Frequency	500 MHz
Bend radius (min)	1.5 cm
Operational conditions	
Operating temperature (T-T)	-25 - 75 °C
Certificates	
Compliance certificates	CE, RoHS
Weight & dimensions	
Outer diameter	3.8 mm
Packaging content	
Quantity per pack	1 pc(s)
Logistics data	
Warranty period	5 year(s)

Technical details	
Sustainability compliance	Yes

Gamintojo ir saugos informacija

GAMINTOJAS

Intronics BV

Koolhovenstraat 1E, 3772 MT Barneveld, NL

intronics.nl

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt