

ACT Black 5 meters U/UTP CAT6A LSZH Slimline patch cable with RJ45 connectors 90° angled right to straight

Gamintojas: **ACT** · Modelis: **DC2905** · EAN: **8716065547184** · Prekės kodas: **965198**



17,90 €

Kaina su PVM

Be PVM: **14,79 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Straight RJ45 to 90° angled right RJ45 connectors
- ✓ Ideal for situations where space is limited without stressing the bend radius
- ✓ Full copper 28AWG wires, 50μ gold-plated RJ45 contacts
- ✓ Outer diameter jacket of only 3.6mm to improve airflow in cabinets
- ✓ Low Smoke Zero Halogen (LSZH) cable jacket reduces the risk of high concentrations of toxic gases in case of cable damage due to fire or short circuit
- ✓ Conforms to international standard ANSI/TIA-568.2-D
- ✓ Cables are 100% tested
- ✓ Colour: Black





Aprašymas

CAT6A U/UTP slimline datacenter patch cables are smaller in diameter (3.6mm vs 5.9mm) than regular CAT6A patch cords. The bend radius is smaller compared to standard patch cords. This results in better airflow in the server rack or network cabinet.

The patch cable has a straight RJ45 connector and a 90° angled right RJ45 connector. Ideal for situations where space is limited without compromising the bend radius. For example in network cabinets and behind equipment.

Also available with a straight to 90° angled up, down or left RJ45 connector.

The use of a LSZH (Low Smoke Zero Halogen) cable jacket reduces the risk of high concentrations of toxic gases if the cable is damaged by fire or short circuit.

The ACT U/UTP patch cable has full copper 28AWG wires and 50μ gold-plated RJ45 contacts and complies with the international standard ANSI/TIA-568.2-D.

Techninė specifikacija

Features	
Cable length	5 m
Cable standard	Cat6a
Cable shielding	U/UTP (UTP)
Connector 1	RJ-45
Connector 2	RJ-45
Product colour	Black
Connector 1 gender	Male
Connector 2 gender	Male
Connector 1 form factor	Straight
Connector 2 form factor	Angled
Connector contacts plating	Gold
Jacket material	Low smoke zero halogen (LSZH)
Cable shape	Round
Conductor material	Copper
Cable type	Straight-through cable
AWG wire size	28
Frequency	500 MHz

Bend radius (min)	1.5 cm
Operational conditions	
Operating temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	40 - 60%
Storage relative humidity (H-H)	40 - 60%
Certificates	
Compliance certificates	CE, UKCA
Certification	CE, ANSI/TIA-568.2-D
Weight & dimensions	
Outer diameter	3.6 mm
Packaging content	
Quantity per pack	1 pc(s)
Other features	
Impedance	100 Ω
Logistics data	
Warranty period	5 year(s)
Technical details	
Sustainability compliance	Yes

Dokumentai ir vaizdo įrašai

- › Gaminio lankstinukas
- › CE ženklimas

Gamintojo ir saugos informacija

GAMINTOJAS
Intronics BV
Koolhovenstraat 1E, 3772 MT Barneveld, NL
intronics.nl

PLATINTOJAS
MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

- › CE ženklimas