ACT Blue 30 meters S/FTP CAT6A B2ca PoE++ 100W solid prefab installation cable, RJ45 male – female

Gamintojas: **ACT** · Modelis: **FB0130** · EAN: **8716065587838** · Prekės kodas: **965520**



105,90 €

Kaina su PVM

Be PVM: **87,52 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Cable length: 30 meters
- ✓ Full copper S/FTP CAT6A solid cable with RJ45 connectors, suitable for CPR Euroclass B2ca and 100W PoE++ applications
- ✓ Easily expand your network with pre-terminated cabling; Plug and play, no tooling or technical knowledge required
- ✓ Highest fire class performance, CPR Euroclass: B2ca, s1a, d0, a1; suitable for installation in high risk environments
- ✓ Declaration of Performance (DoP) number: 1320-2406
- ✓ IDC connectors: optimal connection for 4PPoE 100W PoE++ (type 4)
- ✓ Full copper 23AWG wires, 50µ gold-plated RJ45 contacts
- ✓ Complies with international standards ANSI/TIA-568.2-D and ISO/IEC 11801-1
- ✓ Suitable for HDBaseT applications
- ✓ Available in lengths up to 90 meters, male-male and female-female



Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.





Aprašymas

The S/FTP CAT6A prefab solid installation cable is suitable for all applications and buildings, including high risk environments, thanks to its CPR Euroclass B2ca rating. The cable supports 4PPoE / PoE++ 100W applications. The installation cable features full copper 23AWG wires and 50µ gold-plated RJ45 contacts attached via IDC, and complies with international standards ANSI/TIA-568.2-D and ISO/IEC 11801-1.

Pre-terminated solid installation cables

The ACT prefab CAT6A solid installation cables are ready for immediate use. The RJ45 connectors are pre-terminated which eliminates the risk of errors during field installation. Additionally, no assembling or termination time is required, and no special tools are needed.

These solid installation cables are designed for 100W Power over Ethernet applications due to the use of IDC (Insulation Displacement Contacts). This prefab cable assembly has 23AWG copper core wires and IDC connectors, and thereby ensures a stable and long-lasting network connection in 4PPoE 100W (type 4) applications.

Euroclass B2ca: suitable for high-risk environments

These pre-terminated installation cables meet the highest CPR rating: Euroclass B2ca, making them suitable for installation in all buildings and applications, including high-risk environments such as data centers, server rooms, commercial buildings, healthcare facilities and educational facilities.

Declaration of Performance

The ACT pre-terminated solid CAT6A cables with RJ45 connectors meet all the requirements, fire safety, mechanical resistance, and durability, as specified in the European Construction Products Regulation (CPR). These cables are guaranteed to comply with the CPR regulation, ensuring reliable and safe performance.

The benefits of pre-terminated S/FTP CAT6A solid cables:
- Easy installation, no experience required
- Meets CPR Euroclass B2ca, the highest EU fire safety standard
- Supports 100W Power over Ethernet
- No specialized technician needed
- No tooling required
- No assembling time
- Easily built and customize your own network

Techninė specifikacija

Features	
Cable length	30 m
Cable standard	Cat6a
Cable shielding	S/FTP (S-STP)

Connector 1	RJ-45
Connector 2	RJ-45
Product colour	Blue
Connector 1 gender	Male
Connector 2 gender	Female
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Gold
Jacket material	Low smoke zero halogen (LSZH)
Cable shape	Round
Conductor type	Solid
Conductor material	Copper
Twisted pair coupling type	4x2
Cable class	Ea
Cable fire class	B2ca
Networking standards	IEEE 802.3bt
AWG wire size	23
Frequency	500 MHz
Bend radius (min)	3 cm
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	PoE++ (4PPoE)
Total Power over Ethernet (PoE) budget	100 W
Plug and Play	Yes
Operational conditions	
Operating temperature (T-T)	-10 - 60 °C
Storage temperature (T-T)	-40 - 70 °C
Certificates	
Compliance certificates	ANSI, CE, Telecommunicatios Industry Association (TIA), UKCA
Weight & dimensions	
Outer diameter	7.4 mm
Packaging content	
Quantity per pack	1 pc(s)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

Intronics BV
Koolhovenstraat 1E, 3772 MT Barneveld, NL
intronics.nl

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt