TP-Link Omada EAP100-BRIDGE KIT bridge/repeater Network bridge 300 Mbit/s White

Gamintojas: **TP-LINK** · Modelis: **EAP100-BRIDGE KIT** · EAN: **1210002603768** · Prekės kodas: **968854**

125,90 €

Kaina su PVM

Be PVM: **104,05 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Up to 1640 ft (500 m) Wi-Fi transmission
- ✓ Equipped with Omada SmartBridging: Our unique design for the most effortless and easy bridge setup ever.
- ✓ Plug-and-Play Preconfigured Kit: Preconfigured for instant auto-pairing, the bridges deliver instant connectivity right out of the box. Simply power on and go. Ideal for quick deployments.
- ✓ App-Guided Alignment: Visualized App-Guided Alignment for long-distance setups and Instant Speed Testing for installation verification.
- ✓ Flexible Power Supply: 802.3af PoE, 24V Passive PoE, and 12V DC (compatible with TP-Link solar power supply systems).
- ✓ 3× Fast Ethernet Ports: Connects more cameras and devices without an extra switch.
- ✓ Built for Tough Outdoor Conditions: Features an IP65 weatherproof enclosure and operating range of -40℉ to +158 ℉.
- ✓ Remote Monitoring & Management: Choose Standalone mode or Omada SDN mode for remote centralized management via Web UI or app.

Aprašymas

Seamless Point-to-Point Connections

Enjoy reliable network performance up to 1640 ft (500 m) transmission distance.

Techninė specifikacija

Data transmission	
Maximum data transfer rate	300 Mbit/s
Maximum transfer distance	500 m
Antenna	
Antenna design	Internal
Antenna type	2x2
Antenna gain level (max)	8 dBi
Wireless LAN features	
Wi-Fi	Yes
Top Wi-Fi standard	Wi-Fi 4 (802.11n)
Network	
Ethernet LAN	Yes
Ethernet LAN interface type	Fast Ethernet
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3af
Ports & interfaces	
Ethernet LAN (RJ-45) ports	3
Security	
MAC address filtering	Yes
Management features	
Web-based management	Yes
Features	
Product type	Network bridge
Mounting type	Wall/Pole
Product colour	White
Reset button	Yes
International Protection (IP) code	IP65
Power	
DC input voltage	12 V
Power consumption (max)	4.8 W
Power over Ethernet (PoE)	Yes
Operational conditions	
Operating temperature (T-T)	-40 - 70 °C

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Operating temperature (T-T)	-40 - 158 °F
Operating relative humidity (H-H)	10 - 90%
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 90%
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
Weight & dimensions	
Width	79 mm
Depth	60 mm
Height	224 mm
Packaging data	
Quantity per pack	2 pc(s)

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH
Niederkasseler Lohweg 175, 40547 Düsseldorf, DE
tp-link.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.