Thermaltake Toughpower GX3 SE 750W power supply unit 24-pin ATX ATX Black

Gamintojas: **THERMALTAKE** · Modelis: **PS-TPD-0750NNSAGE-3** · EAN: **4711658549136** · Prekės kodas: **970948**



82,90 €

Kaina su PVM

Be PVM: **68,51 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt











Aprašymas

Compliance certificates: Low Voltage Directive (LVD) | PCI Express power connectors (12+4 pin): 1 | Combined power (+3.3V): 110 W | Max output current (+12V): 62.5 A | Max output current (-12V): 0.3 A | Max output current (+3.3V): 18 A | PCI Express connector: Yes | Peripheral (Molex) power cable length: 150 mm | SATA power cable length: 150 mm | Compliance certificates: CE | Power Factor Correction (PFC) type: Active | Compliance certificates: RCM | Compliance certificates: BIS | Motherboard power cable length: 50 cm | Combined power (-12V): 3.6 W | Compliance certificates: UKCA | Compliance certificates: CB | Combined power (+12V): 750 W | Peripheral (Molex) power cable length: 450 | SATA power cable length: 450 | Number of SATA power connectors: 3 | Combined power (+5V): 110 W | PCI Express power connectors (6+2 pin): 4 | Bearing technology: FDB | Max output current (+5Vsb): 3 A | Combined power (+5Vsb): 15 W | Hold time: 17 ms | Power supply unit (PSU) form factor: ATX | Max output current (+5V): 18 A | PCI Express power connectors (12+4 pin) cable length: 600 mm | EPS power connector (4+4 pin): Yes | ATX version: 3.1 | Power Good signal delay range: 100 - 150 ms | Motherboard power connector: 24-pin ATX | Height: 86 mm | Product colour: Black | Input current: 6 A | 80 PLUS certification: 80 PLUS Gold | Storage temperature (T-T): -40 - 55 °C | AC input voltage: 200 - 240 V | Purpose: PC | Mean time between failures (MTBF): 100000 h | Peripheral (Molex) power connectors (4-pin): 1 | Power protection features: Over power | Power protection features: Short circuit |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Power protection features: Over voltage | Power protection features: Under voltage | Power protection features: Over current | Power protection features: Overheating | Package type: Box | Operating temperature (T-T): 5 - 40 °C | Cooling type: Active | Efficiency: 90% | Depth: 140 mm | AC input frequency: 50/60 Hz | Storage relative humidity (H-H): 10 - 95% | Cabling type: Non-Modular | Width: 150 mm | Operating relative humidity (H-H): 20 - 85% | Total power: 750 W | Fan diameter: 12 cm | On/off switch: Yes | Number of fans: 1 fan(s)

Techninė specifikacija

Matmenys ir svoris	
Matmenys (I × P × A)	29,00cm × 13,00cm × 22,00cm
Svoris	2,25kg

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903