Thermaltake Toughpower GX3 SE 850W power supply unit 24-pin ATX ATX Black

Gamintojas: **THERMALTAKE** · Modelis: **PS-TPD-0850NNSAGE-3** · EAN: **4711658549181** · Prekės kodas: **970949**



90,90 €

Kaina su PVM

Be PVM: **75,12 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt











Aprašymas

Peripheral (Molex) power cable length: 150 mm | PCI Express connector: Yes | Peripheral (Molex) power cable length: 450 | Number of SATA power connectors: 3 | PCI Express power connectors (12+4 pin): 1 | Motherboard power connector: 24-pin ATX | Compliance certificates: CB | PCI Express power connectors (12+4 pin) cable length: 600 mm | Compliance certificates: Low Voltage Directive (LVD) | Compliance certificates: UKCA | Power Good signal delay range: 100 - 150 ms | Compliance certificates: RCM | Compliance certificates: BIS | Compliance certificates: CE | EPS power connector (4+4 pin): Yes | Package type: Box | Storage temperature (T-T): -40 - 55 °C | Input current: 6 A | Product colour: Black | AC input voltage: 200 - 240 V | Operating temperature (T-T): 5 - 40 °C | Cooling type: Active | AC input frequency: 50/60 Hz | Operating relative humidity (H-H): 20 - 85% | Peripheral (Molex) power connectors (4-pin): 1 | Storage relative humidity (H-H): 10 - 95% | Combined power (+12V): 850 W | Number of fans: 1 fan(s) | Max output current (+5Vsb): 3 A | Width: 150 mm | Max output current (+3.3V): 18 A | Hold time: 17 ms | Power supply unit (PSU) form factor: ATX | Max output current (-12V): 0.3 A | Power protection features: Short circuit | Power protection features: Over voltage | Power protection features: Over power | Motherboard power cable length: 50 cm | Power protection features: Overheating | Combined power (+5V): 110 W | Cabling type: Non-Modular | Total power: 850 W | SATA power cable length: 150 mm | Power protection features: Under voltage | Power protection features:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Over current | Combined power (-12V): 3.6 W | SATA power cable length: 450 | Combined power (+5Vsb): 15 W | Bearing technology: FDB | On/off switch: Yes | PCI Express power connectors (6+2 pin): 4 | Combined power (+3.3V): 110 W | Purpose: PC | Height: 86 mm | Max output current (+12V): 70.8 A | Mean time between failures (MTBF): 100000 h | 80 PLUS certification: 80 PLUS Gold | Power Factor Correction (PFC) type: Active | Fan diameter: 12 cm | ATX version: 3.1 | Max output current (+5V): 18 A | Efficiency: 90% | Depth: 140 mm

Techninė specifikacija

Matmenys ir svoris	
Matmenys (I × P × A)	29,00cm × 13,00cm × 22,00cm
Svoris	2,24kg

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903